

# SAFETY DATA SHEET

Version 6.4 Revision Date 02/25/2021 Print Date 03/01/2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : tert-Butyl ethyl ether

Product Number : 442795 Brand : Supelco CAS-No. : 637-92-3

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

# 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor. H336 May cause drowsiness or dizziness.

Supelco - 442795

Millipore Sigma

Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
	smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
	clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable
	for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant
	foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal
	plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Component	Classification	Concentration			
2-Ethoxy-2-methylpropane					
	Flam. Liq. 2; STOT SE 3;	<= 100 %			
	H225, H336				

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

# **General advice**

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Supelco - 442795

Millipore SigMa

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

## Suitable extinguishing media

Dry powder Dry sand

## Unsuitable extinguishing media

Do NOT use water jet.

# 5.2 Special hazards arising from the substance or mixture

Carbon oxides

#### **5.3** Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

## **6.2 Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

# **6.4** Reference to other sections

For disposal see section 13.



## **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

## Advice on safe handling

Avoid inhalation of vapor or mist.

## Advice on protection against fire and explosion

Use explosion-proof equipment. **Advice on protection against fire and explosion**Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

#### **Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

## Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Store at room temperature.

Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
2-Ethoxy-2- methylpropane	637-92-3	TWA	25 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Not classifiable as a human carcinogen			
		PEL	5 ppm 21 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

# 8.2 Exposure controls


## **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).



#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 33 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

# **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### **SECTION 9: Physical and chemical properties**

# 0.1 Information on basic physical and chemical properties

a) Appearance Form: clear, liquid

Color: colorless

b) Odorc) Odor Thresholdd) pHNo data availableNo data available

e) Melting point/range: -97 °C (-143 °F) - lit.

point/freezing point

f) Initial boiling point 72 - 73 °C 162 - 163 °F - lit.

and boiling range

Supelco - 442795

Millipore SigMa g) Flash point -19 °C (-2 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower No data available flammability or

k) Vapor pressure 207 hPa at 25 °C (77 °F)

I) Vapor density No data availablem) Relative density 0.75 at 15 °C (59 °F)

n) Water solubility 14.3 g/l at 25.00 °C (77.00 °F) - OECD Test Guideline 105

o) Partition coefficient: log Pow: 1.48 at 25 °C (77 °F)

n-octanol/water

explosive limits

p) Autoignition 392 °C (738 °F) at 1003.40 - 1009.20 hPa temperature

q) Decomposition No data available temperature

r) Viscosity 0.53 mm2/s at 20 °C (68 °F) -

s) Explosive properties No data availablet) Oxidizing properties No data available

# 9.2 Other safety information

Surface tension 72.1 mN/m at 21 °C (70 °F)

#### **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No data available

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

## 10.4 Conditions to avoid

Heat, flames and sparks.

## 10.5 Incompatible materials

Strong oxidizing agents

#### 10.6 Hazardous decomposition products

In the event of fire: see section 5



# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

## **Acute toxicity**

LD50 Oral - Rat - male and female - > 2,003 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - > 5.88 mg/l

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

No data available

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

# Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 4 h (OECD Test Guideline 405)

## Respiratory or skin sensitization

Maximization Test - Guinea pig Result: Not a skin sensitizer. (OECD Test Guideline 406)

## Germ cell mutagenicity

Ames test S. typhimurium Result: negative

Ames test

Salmonella typhimurium

Result: negative

unscheduled DNA synthesis assay

Escherichia coli Result: positive

Rat - male and female - Bone marrow

Result: negative

Remarks: (ECHA)

Rat - male and female - Bone marrow

Result: negative

Remarks: (ECHA)

## Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Supelco - 442795

# Reproductive toxicity

No data available

## Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

## Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

#### 11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Inhalation - 90 dRemarks: Subchronic toxicity

Repeated dose toxicity - Rat - male and female - Oral - 182 d - NOAEL (No observed adverse effect level) - 100 mg/kg

Repeated dose toxicity - Rat - male and female - Inhalation - 104 Weeks

RTECS: KN4730200

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish semi-static test LC50 - Poecilia reticulata (guppy) - > 974.1 mg/l -

96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 110 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test NOEC - Pseudokirchneriella subcapitata (green algae) - 7.5

mq/l - 72 h

(OECD Test Guideline 201)

static test EC50 - Pseudokirchneriella subcapitata (algae) - 1,100

mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - Pseudomonas putida - 510 mg/l - 16 h

(ISO 10712)

static test NOEC - Pseudomonas putida - 78 mg/l - 16 h

(ISO 10712)

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 14 d

Result: 94.16 % - Readily biodegradable.

(OECD Test Guideline 301D)

Supelco - 442795

# 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Contact a licensed professional waste disposal service to dispose of this material.

### Contaminated packaging

Dispose of as unused product.

## **SECTION 14: Transport information**

DOT (US)

UN number: 3271 Class: 3 Packing group: II

Proper shipping name: Ethers, n.o.s.

Reportable Quantity (RQ): Poison Inhalation Hazard: No

**IMDG** 

UN number: 3271 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ETHERS, N.O.S. (2-Ethoxy-2-methylpropane)

**IATA** 

UN number: 3271 Class: 3 Packing group: II Proper shipping name: Ethers, n.o.s. (2-Ethoxy-2-methylpropane)

# **SECTION 15: Regulatory information**

#### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# SARA 311/312 Hazards

Supelco - 442795

Page 9 of 10

Fire Hazard

## **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

2-Ethoxy-2-methylpropane	CAS-No. 637-92-3	Revision Date 2010-08-02
2-Ethoxy-2-methylpropane	CAS-No. 637-92-3	Revision Date 2010-08-02
New Jersey Right To Know Components 2-Ethoxy-2-methylpropane	CAS-No. 637-92-3	Revision Date 2010-08-02

# **SECTION 16: Other information**

#### **Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4 Revision Date: 02/25/2021 Print Date: 03/01/2022

