

Safety Data Sheet AKV908 Date of issue: 05/24/2017 Version: 1.0

## **SECTION 1: Identification**

#### Identification

Product name : VANADIUM TRIISOBUTOXIDE OXIDE, 95%

: AKV908 Product code Product form : Substance Physical state : Liquid Formula : C12H27O4V

VANADIC ACID, TRIISOBUTYL ESTER Synonyms

TRIS(2-METHYLPROPAN-1-OLATO)OXOVANADIUM VANADIC ACID (H3VO4), TRIS(2-METHYLPROPYL) ESTER VANADIUM, TRIS(2-METHYL-1-PROPANOLATO)OXO-, (T-4)-VANADIUM OXIDÈ TRIISOBUTYLATE, VANADYL ISOBUTYLATE

: METAL COMPOUND Chemical family

#### Recommended use and restrictions on use

Recommended use : Chemical intermediate

#### 1.3. **Supplier**

#### **GELEST, INC.**

11 East Steel Road Morrisville, PA 19067

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

#### **Emergency telephone number**

**Emergency number** : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

#### **SECTION 2: Hazard(s) identification**

#### 2.1. Classification of the substance or mixture

## **GHS-US** classification

Flammable liquids Category 3 H226 Flammable liquid and vapor Acute toxicity (oral) Category 3 H301 Toxic if swallowed Acute toxicity (dermal) Category 4 H312 Harmful in contact with skin Skin corrosion/irritation Category 2 H315 Causes skin irritation H319 Causes serious eye irritation Serious eye damage/eye irritation Category 2 H335 May cause respiratory irritation

Specific target organ toxicity (single exposure) Category 3

Full text of H statements : see section 16

#### GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

H226 - Flammable liquid and vapor Hazard statements (GHS US)

H301 - Toxic if swallowed

H312 - Harmful in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P312 - Call a doctor if you feel unwell

P210 - Keep away from heat, open flames, sparks. - No smoking.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

EN (English US) SDS ID: AKV908 Print date: 04/11/2019 Page 1

## Safety Data Sheet

P330 - Rinse mouth.

P301+P310 - If swallowed: Immediately call a doctor

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention. P321 - Specific treatment (see first aid instructions on this label) P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Keep in a cool place

P405 - Store locked up.

P501 - Dispose of contents/container to licensed waste disposal facility.

#### Hazards not otherwise classified (HNOC)

No additional information available

#### **Unknown acute toxicity (GHS US)**

Not applicable

#### **SECTION 3: Composition/Information on ingredients**

#### **Substances**

Substance type : Mono-constituent

VANADIUM TRIISOBUTOXIDE OXIDE, 95% Name

CAS-No. 19120-62-8

Name	Product identifie	r %	GHS-US classification
Vanadium triisobutoxide oxide	(CAS-No.) 19120-62-8	95 - 100	Flam. Liq. 3, H226
			Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312
		y	Skin Irrit. 2, H315
			Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

## **Mixtures**

Not applicable

## **SECTION 4: First-aid measures**

### **Description of first aid measures**

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact Wash with plenty of soap and water. Immediately call a poison center or doctor/physician.

First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion Never give anything by mouth to an unconscious person. Immediately call a poison center or

doctor/physician.

#### Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation. Harmful in contact with skin.

Symptoms/effects after eye contact Causes serious eye irritation.

Symptoms/effects after ingestion Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

## Immediate medical attention and special treatment, if necessary

No additional information available

## **SECTION 5: Fire-fighting measures**

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

## Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when

material is exposed to elevated temperatures or open flame.

Print date: 04/11/2019 EN (English US) SDS ID: AKV908 2/7

## Safety Data Sheet

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-

sparking tools.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

#### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from

heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and

receiving equipment. Take precautionary measures against static discharge. Use only outdoors

or in a well-ventilated area. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof

electrical equipment.

Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.

Incompatible materials : Moist air. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Vanadium triisobutoxide oxide (19120-62-8)		
OSHA	OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ V205

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Handle in an enclosing hood with exhaust ventilation.

## 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

Print date: 04/11/2019 EN (English US) SDS ID: **AKV908** 3/7

## Safety Data Sheet

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Molecular mass : 286.29 g/mol
Color : Yellow.

Odor : characteristic. Isobutanol.

Odor threshold : No data available

Refractive index : 1.487

pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : -10 - -5 °C

Freezing point : No data available
Boiling point : 105 °C @ 1.5 mm Hg

Flash point : 27.8 °C

Auto-ignition temperature : No data available
Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : <1 mm Hg @ 25°C

Relative vapor density at 20 °C : > 1
Relative density : 1.011

Reacts with water. Solubility Log Pow No data available No data available Log Kow Viscosity, kinematic No data available Viscosity, dynamic No data available Explosive properties No data available : No data available Oxidizing properties **Explosion limits** : No data available

### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Stable in sealed containers.

#### 10.3. Possibility of hazardous reactions

Material reacts rapidly with water or moist air, liberating isobutanol and vanadium oxide gel.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

#### 10.5. Incompatible materials

Moist air. Water.

## 10.6. Hazardous decomposition products

Organic acid vapors. Vanadium oxide fumes.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

Print date: 04/11/2019 EN (English US) SDS ID: **AKV908** 4/7

## Safety Data Sheet

VANADIUM TRIISOBUTOXIDE OXIDE, 95% (19120-62-8)		
ATE US (oral)	293 mg/kg body weight	
ATE US (dermal)	1930 mg/kg body weight	
Vanadium triisobutoxide oxide (19120-62-8)		
LD50 oral rat	293 mg/kg RTECS Number: YW1115000	
LD50 dermal rabbit	1930 mg/kg	
ATE US (oral)	293 mg/kg body weight	
ATE US (dermal)	1930 mg/kg body weight	
Older and the Control of the control	Once an additional form	

Skin corrosion/irritation : Causes skin irritation.

Skin Irritation - rabbit: 100 mg: severe irritation effect

Serious eye damage/irritation : Causes serious eye irritation.

Eye Irritation - rabbit: 500 mg/24H: severe irritation effect

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP,

OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation. Harmful in contact with skin.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

### **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## **SECTION 14: Transport information**

## 14.1. UN number

UN-No.(DOT) : 1992 DOT NA no. UN1992

### 14.2. UN proper shipping name

Transport document description : UN1992 Flammable liquids, toxic, n.o.s. (VANADIUM TRIISOBUTOXIDE OXIDE), 3 (6.1), III

Print date: 04/11/2019 EN (English US) SDS ID: **AKV908** 5/7

## Safety Data Sheet

Proper Shipping Name (DOT) : Flammable liquids, toxic, n.o.s.

(VANADIUM TRIISOBUTOXIDE OXIDE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid

6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

## Vanadium triisobutoxide oxide (19120-62-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

## CANADA

## Vanadium triisobutoxide oxide (19120-62-8)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### **EU-Regulations**

#### Vanadium triisobutoxide oxide (19120-62-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **National regulations**

## Vanadium triisobutoxide oxide (19120-62-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## **SECTION 16: Other information**

## Full text of H-phrases::

A of the prince		
H226	Flammable liquid and vapor	
H301	Toxic if swallowed	
H312	Harmful in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	

Print date: 04/11/2019 EN (English US) SDS ID: **AKV908** 6/7

Safety Data Sheet

H335 May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

#### **Hazard Rating**

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above

100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 05/24/2017 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 04/11/2019 EN (English US) SDS ID: **AKV908** 7/7