SAFETY DATA SHEET

Version 5.7 Revision Date 09/23/2016 Print Date 10/09/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : 1,1-Dichloropropene

Product Number : 41166 Brand : Supelco

CAS-No. : 563-58-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich

3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled

H370 Causes damage to organs.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

Supelco - 41166 Page 1 of 10

| Take precautionary measures against static discharge. |
|---|
| Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. |
| Wash skin thoroughly after handling. |
| Do not eat, drink or smoke when using this product. |
| Use only outdoors or in a well-ventilated area. |
| Wear protective gloves/ eye protection/ face protection. |
| IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. |
| IF ON SKIN (or hair): Remove/ Take off immediately all contaminated |
| clothing. Rinse skin with water/ shower. |
| IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. |
| IF exposed: Call a POISON CENTER or doctor/ physician. |
| Wash contaminated clothing before reuse. |
| In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. |
| Store in a well-ventilated place. Keep container tightly closed. |
| Store in a well-ventilated place. Keep cool. |
| Store locked up. |
| Dispose of contents/ container to an approved waste disposal plant. |
| |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Synonyms : 1,1-Dichloro-1-propene

Formula : $C_3H_4Cl_2C_3H_4Cl_2$ Molecular weight : 110.97 g/mol

Hazardous components

| Component | | Classification | Concentration |
|---------------------|-----------------------|-----------------------------|----------------|
| Methanol | | | |
| CAS-No. | 67-56-1 | Flam. Liq. 2; Acute Tox. 3; | >= 90 - <= 100 |
| EC-No. | 200-659-6 | STOT SE 1; H225, H301 + | % |
| Index-No. | 603-001-00-X | H311 + H331, H370 | |
| Registration number | 01-2119433307-44-XXXX | | |
| 1,1-Dichloropropene | | | |
| CAS-No. | 563-58-6 | Flam. Liq. 2; Acute Tox. 3; | >= 0.1 - < 1 % |
| EC-No. | 209-253-3 | Aquatic Acute 3; Aquatic | |
| Index-No. | 602-031-00-0 | Chronic 3; H225, H301, H412 | |
| | | | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

Supelco - 41166 Page 2 of 10

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eves. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Supelco - 41166 Page 3 of 10

| Component | CAS-No. | Value | Control parameters | Basis | |
|-----------|---------|---|---|--|--|
| Methanol | 67-56-1 | TWA | 200.000000 ppm | USA. ACGIH Threshold Limit Values (TLV) | |
| | Remarks | Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption | | | |
| | | STEL | 250.000000 ppm | USA. ACGIH Threshold Limit Values (TLV) | |
| | | Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Index or See BEI® section) Danger of cutaneous absorption | | | |
| | | TWA | 200.000000 ppm 260.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits | |
| | | Potential for | | | |
| | | ST | 250.000000 ppm 325.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits | |
| | | Potential for | dermal absorption | | |
| | | TWA | 200.000000 ppm 260.000000 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants | |
| | | The value in | lue in mg/m3 is approximate. | | |
| | | TWA | 200 ppm | USA. ACGIH Threshold Limit Values (TLV) | |
| | | (see BEI® s | ess mage nces for which there is a Biological Exposure Index or Indices | | |
| | | STEL | 250 ppm | USA. ACGIH Threshold Limit Values (TLV) | |
| | | Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption | | | |
| | | TWA | 200 ppm 260 mg/m3 | USA. NIOSH Recommended Exposure Limits | |
| | | Potential for dermal absorption | | | |

Supelco - 41166 Page 4 of 10

| ST | 250 ppm 325 mg/m3 | USA. NIOSH Recommended Exposure Limits | | |
|-----------|------------------------------------|---|--|--|
| Potential | Potential for dermal absorption | | | |
| TWA | 200 ppm 260 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants | | |
| The value | The value in mg/m3 is approximate. | | | |
| STEL | 250 ppm 325 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 | | |
| Skin nota | Skin notation | | | |
| TWA | 200 ppm 260 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 | | |
| Skin nota | Skin notation | | | |
| С | 1,000 ppm | California permissible exposure limits for chemical contaminants (Title 8, Article 107) | | |
| Skin | | | | |
| PEL | 200 ppm 260 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) | | |
| Skin | | | | |
| STEL | 250 ppm 325 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) | | |
| Skin | | | | |

Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|-----------|---------|--|--|---------------------|---|
| Methanol | 67-56-1 | Methanol | 15.0000 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | End of shift (A | End of shift (As soon as possible after exposure ceases) | | |
| | | Methanol | 15 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | | End of shift (As soon as possible after exposure ceases) | | | |

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Supelco - 41166 Page 5 of 10

Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Form: liquid a) Appearance

Colour: colourless

b) Odour No data available Odour Threshold No data available No data available d) рΗ

Melting point/freezing

Melting point/range: -98 °C (-144 °F)

point

Initial boiling point and

boiling range

64 - 65 °C (147 - 149 °F) at 1,013 hPa (760 mmHg)

Flash point 11 °C (52 °F) - closed cup

h) Evaporation rate No data available Flammability (solid, gas) No data available

Upper explosion limit: 36 %(V) Upper/lower flammability or Lower explosion limit: 6 %(V)

explosive limits

Vapour pressure 130.23 hPa (97.68 mmHg) at 20 °C (68 °F) k)

547 hPa (410 mmHg) at 50 °C (122 °F)

Vapour density No data available I)

m) Relative density 0.791 g/cm3

n) Water solubility completely miscible o) Partition coefficient: n-No data available

octanol/water

p) Auto-ignition 385 °C (725 °F)

temperature Decomposition

temperature

No data available

Viscosity No data available r)

Supelco - 41166 Page 6 of 10 s) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Acid chlorides, Acid anhydrides, Reducing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

Supelco - 41166 Page 7 of 10

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, May cause convulsions.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: Methanol, solution

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOL, SOLUTION

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II

Supelco - 41166 Page 8 of 10

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date

Methanol 67-56-1 2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

 CAS-No.
 Revision Date

 Methanol
 67-56-1
 2007-07-01

Pennsylvania Right To Know Components

 CAS-No.
 Revision Date

 Methanol
 67-56-1
 2007-07-01

New Jersey Right To Know Components

CAS-No. Revision Date Methanol 67-56-1 2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the CAS-No. Revision Date State of California to cause birth defects or other reproductive 67-56-1 2012-03-16

harm. Methanol

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Acute toxicity

Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity
Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301 + H311 + Toxic if swallowed, in contact with skin or if inhaled

H331

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H412 Harmful to aquatic life with long lasting effects.
STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Supelco - 41166 Page 9 of 10

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.7 Revision Date: 09/23/2016 Print Date: 10/09/2017

Supelco - 41166 Page 10 of 10