

**NICKEL FORMATE, dihydrate**

Safety Data Sheet CXNI045

Date of issue: 07/15/2016

Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name : NICKEL FORMATE, dihydrate
 Product code : CXNI045
 Product form : Substance
 Physical state : Solid
 Formula : $C_2H_2NiO_4 \cdot 2H_2O$
 Synonyms : FORMIC ACID, NICKEL SALT
 Chemical family : METAL COMPOUND

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier**GELEST, INC.**

11 East Steel Road
 Morrisville, PA 19067
 USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Skin corrosion/irritation Category 2 H315 Causes skin irritation
 Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation
 Respiratory sensitization, Category 1 H334 May cause an allergy or asthma symptoms or breathing difficulties if inhaled
 Carcinogenicity Category 1A H350 May cause cancer
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled
 H350 - May cause cancer

Precautionary statements (GHS US) :

P202 - Do not handle until all safety precautions have been read and understood.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P261 - Avoid breathing dust.
 P264 - Wash hands thoroughly after handling.
 P284 - [In case of inadequate ventilation] wear In case of inadequate ventilation wear respiratory protection..
 P302+P352 - If on skin: Wash with plenty of soap and water
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P321 - Specific treatment (see first aid instructions on this label)
 P342+P311 - If experiencing respiratory symptoms: Call a doctor
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P405 - Store locked up.
 P501 - Dispose of contents/container to licensed waste disposal facility.

NICKEL FORMATE, dihydrate

Safety Data Sheet

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : NICKEL FORMATE, dihydrate
CAS-No. : 3349-06-2

Name	Product identifier	%	GHS-US classification
Nickel formate, dihydrate	(CAS-No.) 3349-06-2	95 - 100	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause cancer. May cause an allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

Chronic symptoms : Some nickel organic salts have been reported to be experimental neoplastigens and tumorigens. No testing has been conducted on nickel pentanedionate. Nickel formate should be handled as a carcinogen.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid contact with skin and eyes. Do not breathe dust.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

NICKEL FORMATE, dihydrate

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust. Avoid dust formation. Provide local exhaust or general room ventilation to minimize exposure to dust.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Store locked up.

Incompatible materials : Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nickel formate, dihydrate (3349-06-2)

OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³ for nickel
------	-------------------------------------	--------------------------------

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified dust and mist (teal cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Molecular mass	: 184.77/202.77 g/mol
Color	: Green-turquoise.
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available

NICKEL FORMATE, dihydrate

Safety Data Sheet

pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 1 mm Hg @ 25°C
Relative vapor density at 20 °C	: No data available
Relative density	: 2.15
% Volatiles	: < 2 %
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Nickel oxide fumes. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

NICKEL FORMATE, dihydrate

Safety Data Sheet

Symptoms/effects after ingestion	: May be harmful if swallowed.
Chronic symptoms	: Some nickel organic salts have been reported to be experimental neoplastigens and tumorigens. No testing has been conducted on nickel pentanedionate. Nickel formate should be handled as a carcinogen.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on the ozone layer	: No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport.

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

NICKEL FORMATE, dihydrate (3349-06-2)	
SARA Section 313 - Emission Reporting	32 % Toxic Release Inventory Reportable Component: Nickel-Category N495

Nickel formate, dihydrate (3349-06-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Nickel formate, dihydrate (3349-06-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Nickel formate, dihydrate (3349-06-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

NICKEL FORMATE, dihydrate

Safety Data Sheet

Nickel formate, dihydrate (3349-06-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Japanese Pollutant Release and Transfer Register Law (PRTR Law)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases::

H315	Causes skin irritation
H319	Causes serious eye irritation
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Prepared by safety and environmental affairs.

Date of issue: 07/15/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067