

SAFETY DATA SHEET

Revision Date 24-Feb-2020 Revision Number 3

1. Identification

Product Name Dysprosium(III) isopropoxide, 5% w/v in toluene/isopropanol

Cat No.: 36585

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Alfa Aesar Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

Emergency Telephone Number

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Reproductive Toxicity

Specific target organ toxicity (single exposure)

Target Organs - Central nervous system (CNS), Respiratory system.

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Neurological effects, Eyes, Ears.

Aspiration Toxicity Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye damage
May cause respiratory irritation
May cause drowsiness or dizziness
Suspected of damaging the unborn child

May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Toluene	108-88-3	47.50
Isopropyl alcohol	67-63-0	47.50
Dysprosium(III) isopropoxide	6742-68-3	5.00

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Most important symptoms and

effects

Difficulty in breathing. Causes eye burns. Causes severe eye damage. Inhalation of high

vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 4 °C / 39.2 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). Dysprosium oxide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Instability Health **Flammability** Physical hazards 3 3

Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm	TWA: 20 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm	
		Ceiling: 300 ppm	TWA: 375 mg/m ³	
		(Vacated) STEL: 150 ppm	STEL: 150 ppm	
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³	
		TWA: 200 ppm		
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 200 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m ³	TWA: 400 ppm	STEL: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m ³	
		(Vacated) STEL: 1225	STEL: 500 ppm	
		mg/m³	STEL: 1225 mg/m ³	
		TWA: 400 ppm	_	
		TWA: 980 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid Appearance Brown

Odor

No information available
Odor Threshold
No information available
Point/Range
No data available
No data available
No information available
No information available

Boiling Point/Range

Flash Point

Evaporation Rate

No information available
4 °C / 39.2 °F

No information available

Flammability (solid,gas)

Not applicable

Flammability or explosive limits

Upper

No data available

Upper
Lower
No data available
No data available
No data available
No information available
Vapor Density
No information available
Specific Gravity
No information available
No information available
No information available

Partition coefficient; n-octanol/waterNo data availableAutoignition TemperatureNo information availableDecomposition TemperatureNo information available

Viscosity

No information available

Molecular FormulaC9 H21 DyO3Molecular Weight339.76

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Moisture sensitive.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Dysprosium oxide

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Dermal LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.Vapor LC50Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat)	72.6 mg/L (Rat)4 h
		12870 mg/kg (Rabbit)	

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

IrritationNo information availableSensitizationNo information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed				
Isopropyl alcohol	67-63-0	Not listed				
Dysprosium(III) isopropoxide	6742-68-3	Not listed				

Mutagenic Effects No information available

Reproductive Effects California Proposition 65. Reproductive toxicity.

Developmental Effects

No information available.

Teratogenicity

No information available.

STOT - single exposure Central nervous system (CNS) Respiratory system

STOT - repeated exposure Neurological effects Eyes Ears

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredness, nausea and vomiting

in a single sing

Other Adverse Effects The toxicological properties have not been fully investigated.

No information available

12. Ecological information

Ecotoxicity

Endocrine Disruptor Information

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna) EC50: = 11.5 mg/L, 48h (Daphnia magna)
Isopropyl alcohol	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

Persistence and Degradability Immiscible with water May persist

Bioaccumulation/ Accumulation N

No information available.

Mobility

Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Toluene	2.7
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-

14. Transport information

DOT

UN-No UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Technical Name (TOLUENE, ISOPROPANOL (ISOPROPYL ALCOHOL))

Hazard Class 3
Packing Group ||

TDG

UN-No UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3 Packing Group II

<u>IATA</u>

UN-No UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Hazard Class 3 Packing Group II

15. Regulatory information

United States of America Inventory

Component	CAS-No	TSCA	TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory Flags
Toluene	108-88-3	X	ACTIVE	-
Isopropyl alcohol	67-63-0	X	ACTIVE	-
Dysprosium(III) isopropoxide	6742-68-3	-	-	_

l egend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Toluene	108-88-3	Х	-	203-625-9	Х	X	Х	Χ	KE-33936
Isopropyl alcohol	67-63-0	Х	-	200-661-7	Х	X	Χ	Χ	KE-29363
Dysprosium(III) isopropoxide	6742-68-3	-	-	-	-	-	-	-	-

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	47.50	1.0
Isopropyl alcohol	67-63-0	47.50	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Toluene	X	1000 lb	X	X

Clean Air Act

Compone	ent	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene)	X		-

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Toluene	1000 lb 1 lb	=

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	Component CAS-No		Prop 65 NSRL	Category	
Toluene	108-88-3	Developmental	-	Developmental	

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Toluene	X	X	X	X	X
Isopropyl alcohol	Х	Х	Х	-	Х

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

Revision Date 24-Feb-2020 Print Date 24-Feb-2020

Revision Summary SDS authoring systems update, replaces ChemGes SDS No. 1,428.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS