

#### 1 Identification

Product identifier

Product name: Barium selenate

Stock number: 44883

**CAS Number:** 7787-41-9 EC number: Index number:

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street

SU BUTIG STEET Ward Hill, MA 01835-8099 Tel: 800-343-0660 Fax: 800-322-4757 Email: tech @alfa.com

www alfa com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

#### 2 Hazard(s) identification

#### Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to the central nervous system, the liver and the digestive system through prolonged or repeated exposure. Route of exposure: Oral, Inhalative.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS) Hazard pictograms





GHS06 GHS08

## Signal word Danger

Hazard statements
H301+H331 Toxic if swallowed or if inhaled.
H373 May cause damage to the central nervous system, the liver and the digestive system through prolonged or repeated exposure. Route of exposure: Oral, Inhalative.

Precautionary statements
P260 Do not breathe dust/fume/gas/mist/vapours/spray. P260 P261

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

D1A - Very toxic material causing immediate and serious toxic effects



Classification system

HMIS ratings (scale 0-4) (Hazardous Materials Identification System)



Health (acute effects) = 3 Flammability = 0

Flammability = 0

Physical Hazard = 1

Other hazards Results of PBT and vPvB assessment PBT: Not applicable.

vPvB: Not applicable.

# 3 Composition/information on ingredients

Chemical characterization: Substances

CAS# Description: 7787-41-9 Barium selenate Identification number(s): EC number: 232-113-8 Index number: 034-002-00-8 Safety Data Sheet per OSHA HazCom 2012

Page 2/5 Printing date 11/24/2015 Reviewed on 06/22/2010

## Product name: Barium selenate

(Contd. of page 1)

#### 4 First-aid measures

Description of first aid measures General information

Immediately remove any clothing soiled by the product.
Remove breathing apparatus only after contaminated clothing has been completely removed.
In case of irregular breathing or respiratory arrest provide artificial respiration.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Do not induce vomiting; immediately call for medical help. Information for doctor

Most important symptoms and effects, both acute and delayed No further relevant information available. Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Toxic metal oxide fume Advice for firefighters Protective equipment: Wear self-contained respirator.

Wear fully protective impervious suit.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions: Do not allow material to be released to the environment without proper governmental permits.

Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards: No special measures required.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

Handling

Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Open and handle container with care.

Information about protection against explosions and fires: No information known.

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: No information known. Further information about storage conditions:

Keep container tightly sealed. Store in cool, dry conditions in well sealed containers.

Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters Components with limit values that require monitoring at the workplace:

Selenium and selenium compounds (as Se)

mg/m3
ACGIH TLV (
Austria MAK 0 0.2 0.1 0.2 Belgium TWA Denmark TWA Finland TWA 0.1 0.1; 0.3-STEL 0.1 0.1-STEL Germany MAK Hungary Japan OEL Korea TLV 0.1 Notherlands MAC-TGG 0.2
Poland TWA 0.1; 0.3-STEL
Sweden NGV 0.1
Switzerland MAK-W 0.1 United Kingdom TWA 0.1 USA PEL 0.2

Barium, and soluble compounds, as Ba

ACGIH TLV 0.5; Not classified as a human carcinogen 0.5 0.5\_

Austria MAK Belgium TWA Denmark TWA 0.5

(Contd. of page 2)

## Product name: Barium selenate

Finland TWA

0.5 0.5 (total dust) 0.5-STEL 0.5 Germany MAK Hungarý Ireland TWA

Note of the second of the seco

United Kingdom LTEL 0.5 USA PEL 0.5 Additional information Additional information: No data

Exposure controls Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use self-contained respiratory protective device in emergency situations.

Protection of hands:

Protection of hands: Impervious gloves

The selection of suitable gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection: Safety glasses

Body protection: Protective work clothing.

#### 9 Physical and chemical properties

Information on basic physical and chemical properties General Information

Appearance: Form:

Color: White Odor: Odor threshold: Not determined Not determined

pH-value: Not applicable. Change in condition

Melting point/Melting range: Boiling point/Boiling range: Decomposes Not determined Sublimation temperature / start: Not determined

Flash point: Not applicable Flammability (solid, gaseous)
Ignition temperature: Not determined. Not determined Decomposition temperature: Not determined Auto igniting: Not determined

Danger of explosion: Explosion limits: Product does not present an explosion hazard.

Lower: Not determined Not determined Upper: Vapor pressure: Density at 20 °C (68 °F): Relative density Not applicable.

4.75 g/cm³ (39.639 lbs/gal) Not determined.

Vapor density Not applicable. Evaporation rate
Solubility in / Miscibility with
Water at 100 °C (212 °F):
Partition coefficient (n-octanol/water): Not applicable.

Viscosity: dynamic: kinematic:

Not applicable. Not applicable. No further relevant information available. Other information

## 10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions No dangerous reactions known

Conditions to avoid No further relevant information available.

Incompatible materials: Oxidizing agents
No information known.

Hazardous decomposition products: Toxic metal oxide fume

## 11 Toxicological information

Information on toxicological effects Acute toxicity:

Toxic if inhaled. Toxic if swallowed.

LD/LC50 values that are relevant for classification: No data Skin irritation or corrosion: Irritant to skin and mucous membranes. Eye irritation or corrosion: Irritating effect.

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: No effects known.

Carcinogenicity:

EPA-D: Not classifiable as to human carcinogenicity: inadequate human and animal evidence of carcinogenicity or no data are available.

(Contd. on page 4)

## Product name: Barium selenate

(Contd. of page 3)

NTP-R: Reasonably anticipated to be a carcinogen: limited evidence from studies in humans or sufficient evidence from studies in experimental animals. IARC-3: Not classifiable as to carcinogenicity to humans.

ACGIH A4: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans and/or animals. Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure:
May cause damage to the central nervous system, the liver and the digestive system through prolonged or repeated exposure. Route of exposure: Oral, Inhalative.

Specific target organ system toxicity - single exposure: No effects known.

Aspiration hazard: No effects known.

Subacute to chronic toxicity:

Barium compounds may cause severe gastroenteritis, including abdominal pain, vomiting and diarrhea, tremors, faintness, paralysis of the arms and legs, and slow or irregular heartbeat. Severe cases may produce collapse and death due to respiratory failure. Soluble barium compounds are more likely to cause these effects than insoluble compounds. Inhalation of fumes may cause sore throat, coughing, labored breathing, and irritation of the respiratory tract as well as the above symptoms.

Sylhionis. Selenium may cause amyotrophic lateral sclerosis, bronchial irritation, gastrointestinal distress, vasopharyngeal irritation, garlic odor on breath and sweat, metallic taste, pallor, irritability, excessive fatique, loss of fingernails and hair, pulmonary edema, anemia and weight loss.

Subacute to chronic toxicity: No effects known.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

#### 12 Ecological information

Toxicity
Aquatic toxicity: No further relevant information available.
Persistence and degradability No further relevant information available.
Bioaccumulative potential No further relevant information available.
Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Very toxic for aquatic organisms
Additional ecological information:

General notes:

Do not allow material to be released to the environment without proper governmental permits.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

May cause long lasting harmful effects to aquatic life. Avoid transfer into the environment.

Very toxic for aquatic organisms

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

## 13 Disposal considerations

Waste treatment methods

Recommendation Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

| 14 | Transport | information |
|----|-----------|-------------|
|    |           |             |

| UN-Number<br>DOT, IMDG, IATA                 | UN3283   |
|--|--|
| UN proper shipping name<br>DOT<br>IMDG, IATA | Selenium compound, solid, n.o.s. (Barium selenate)<br>SELENIUM COMPOUND, SOLID, N.O.S. (Barium selenate) |

#### Transport hazard class(es)

DOT



Class 6.1 Toxic substances. 6.1 (T5) Toxic substances 6.1 Class Label

IMDG, IATA

Class

Packing group DOT, IMDG, IATA

6.1 Toxic substances.

Environmental hazards:

Environmentally hazardous substance, solid

Warning: Toxic substances

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

Special precautions for user EMS Number:

DOT

Marine Pollutant (DOT): No

UN "Model Regulation":

UN3283, Selenium compound, solid, n.o.s. (Barium selenate), 6.1, II

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

(Contd. on page 5)

(Contd. of page 4)

## Product name: Barium selenate

## Hazard pictograms





Signal word Danger Hazard statements

H301+H331 Toxic if swallowed or if inhaled.
H373 May cause damage to the central nervous system, the liver and the digestive system through prolonged or repeated exposure. Route of exposure: Oral, Inhalative.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

#### SARA Section 313 (specific toxic chemical listings)

7787-41-9 Barium selenate

California Proposition 65
Prop 65 - Chemicals known to cause cancer Substance is not listed.
Prop 65 - Developmental toxicity Substance is not listed.
Prop 65 - Developmental toxicity, female Substance is not listed.
Prop 65 - Developmental toxicity, male Substance is not listed.
Information about limitation of use:

En use only by technically qualified individuals.

or use only by technically qualified individuals.

This product contains barium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

This product contains selenium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations
Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.
The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. Conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department
Date of preparation / last revision 11/24/2015 / 
Abbreviations and acronyms:

RID: Reglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Iri Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO: The rechnical Instructions by the "International Civil Aviation Organization" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

VPUS: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

MTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)

USA