

# SAFETY DATA SHEET

Version 6.3 Revision Date 09/18/2021 Print Date 02/05/2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Manganese(III) fluoride

Product Number : 339296 Brand : Aldrich CAS-No. : 7783-53-1

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

# 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Oxidizing solids (Category 2), H272 Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 4), H332 Acute toxicity, Dermal (Category 4), H312

Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram





Signal word	Danger
Hazard statement(s) H272 H301 H312 + H332 H315 H319 H335	May intensify fire; oxidizer. Toxic if swallowed. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.
Precautionary statement(s)	
P210	Keep away from heat.
P220	Keep/Store away from clothing/ combustible materials.
P221	Take any precaution to avoid mixing with combustibles.
P261 P264	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth.
P302 + P352 + P312	IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/doctor if you feel unwell.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Strong hydrogen fluoride-releaser

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

Formula : F<sub>3</sub>Mn

Molecular weight : 111.93 g/mol CAS-No. : 7783-53-1 EC-No. : 232-006-6

Component	Classification	Concentration
Manganese(III) fluoride		
	Ox. Sol. 2; Acute Tox. 3;	<= 100 %
	Acute Tox. 4; Skin Irrit. 2;	
	Eye Irrit. 2A; STOT SE 3;	



H272, H301, H332, H312,	
H315, H319, H335	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

#### **General advice**

Hydrofluoric (HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24 hours depending on the concentration of HF. After decontamination with water, further damage can occur due to penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases. More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician is experienced in this technique, due to the potential for tissue injury from increased pressure. Absorption can readily occur through the subungual areas and should be considered when undergoing decontamination. Prevention of absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and cardiac arrhythmias should be monitored for, since they can occur after exposure. Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

First treatment with calcium gluconate paste. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed No data available

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

# Suitable extinguishing media

Dry powder Dry sand



## 5.2 Special hazards arising from the substance or mixture

Hydrogen fluoride

Manganese/manganese oxides

Not combustible.

Fire-promoting. Keep away from combustible materials.

Combustible.

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

# **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

#### Advice on safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. **Advice on safe handling** 

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

#### Advice on protection against fire and explosion

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Keep away from heat and sources of ignition.

#### Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place.

Millipore SigMa Handle and store under inert gas. Moisture sensitive. Do not store in glass Keep in a dry place.

# Storage class

Storage class (TRGS 510): 5.1B: Oxidizing hazardous materials

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
Manganese(III) fluoride	7783-53-1	TWA	2.5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		С	5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		TWA	2.5 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Not classifiable as a human carcinogen			
		TWA	0.1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
		Not classifiable as a human carcinogen			
		TWA	0.02 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
		Not classifiable as a human carcinogen			



TWA	2.5 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
С	5 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
ST	3 mg/m3	USA. NIOSH Recommended Exposure Limits
PEL	2.5 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
PEL	0.2 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

**Biological occupational exposure limits** 

Biological occupational exposure innits					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Manganese(III) fluoride	7783-53-1	Fluoride	2 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	Prior to shift (16 hours after exposure ceases)			
		Fluoride	3 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)			

#### 8.2 Exposure controls

## **Appropriate engineering controls**

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

# **Personal protective equipment**

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

## **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.



#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

a) Appearance Form: powder

Color: gray

b) Odorc) Odor Thresholdd) pHNo data availableNo data available

e) Melting No data available

point/freezing point

 f) Initial boiling point No data available and boiling range

g) Flash point ()Not applicable h) Evaporation rate No data available

i) Flammability (solid, gas)

No data available

j) Upper/lower flammability or explosive limits No data available

k) Vapor pressure No data availablel) Vapor density No data available

m) Density 3.54 g/cm3 at 25 °C (77 °F) - lit.

Relative density
 No data available
 No data available
 Partition coefficient:
 No data available
 n-octanol/water

p) Autoignition New temperature

No data available

q) Decomposition temperature

No data available

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties The substance or mixture is classified as oxidizing with the

category 2.



## 9.2 Other safety information

No data available

#### **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No data available

## 10.2 Chemical stability

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

No data available

## 10.4 Conditions to avoid

Reacts dangerously with glass.

# 10.5 Incompatible materials

glass

# 10.6 Hazardous decomposition products

In the event of fire: see section 5

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50 Oral - Mouse - 86 mg/kg

Remarks: Behavioral:Somnolence (general depressed activity).

Behavioral: Convulsions or effect on seizure threshold.

Respiratory disorder

LC50 Inhalation - Mouse - 320 mg/m3

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Eye: Other.

Behavioral: Convulsions or effect on seizure threshold.

Lungs, Thorax, or Respiration: Structural or functional change in trachea or bronchi.

LC50 Inhalation - 4 h - 1.5 mg/l

LD50 Dermal - 1,100 mg/kg

No data available

#### Skin corrosion/irritation

No data available

#### Serious eye damage/eye irritation

No data available

#### Respiratory or skin sensitization

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

Aldrich - 339296

Millipore SiGMa identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

## **Reproductive toxicity**

No data available No data available

## Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

## Specific target organ toxicity - repeated exposure

No data available

## **Aspiration hazard**

No data available

#### 11.2 Additional Information

RTECS: OP0882600

Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia. Men exposed to manganese dusts showed a decrease in fertility. Chronic manganese poisoning primarily involves the central nervous system. Early symptoms include languor, sleepiness and weakness in the legs. A stolid mask-like appearance of the face, emotional disturbances such as uncontrollable laughter and a spastic gait with tendency to fall in walking are findings in more advanced cases. High incidence of pneumonia has been found in workers exposed to the dust or fume of some manganese compounds., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Other adverse effects

No data available



## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

# Contaminated packaging

Dispose of as unused product.

## **SECTION 14: Transport information**

## DOT (US)

UN number: 3087 Class: 5.1 (6.1) Packing group: II

Proper shipping name: Oxidizing solid, toxic, n.o.s. (Manganese(III) fluoride)

Reportable Quantity (RQ): Poison Inhalation Hazard: No

#### **IMDG**

UN number: 3087 Class: 5.1 (6.1) Packing group: II EMS-No: F-A, S-Q Proper shipping name: OXIDIZING SOLID, TOXIC, N.O.S. (Manganese(III) fluoride)

#### **IATA**

UN number: 3087 Class: 5.1 (6.1) Packing group: II

Proper shipping name: Oxidizing solid, toxic, n.o.s. (Manganese(III) fluoride)

# **SECTION 15: Regulatory information**

#### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

Manganese(III) fluoride CAS-No. Revision Date 2015-07-08

#### SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

#### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

## **Pennsylvania Right To Know Components**

Manganese(III) fluoride CAS-No. Revision Date 7783-53-1 2015-07-08

Aldrich - 339296

Page 10 of 11



#### **SECTION 16: Other information**

#### **Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3 Revision Date: 09/18/2021 Print Date: 02/05/2022

