

## SAFETY DATA SHEET

Version 8.2  
Revision Date 01/14/2022  
Print Date 06/02/2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : tert-Butanol for analysis EMSURE® ACS

Product Number : 1.09629

Catalogue No. : 109629

Brand : Millipore

Index-No. : 603-005-00-1

CAS-No. : 75-65-0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Reagent for analysis

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-  
527-3887 CHEMTREC (International) 24  
Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225

Acute toxicity, Inhalation (Category 4), H332

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, Central nervous system, H335, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 GHS Label elements, including precautionary statements**

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	: C <sub>4</sub> H <sub>10</sub> O
Molecular weight	: 74.12 g/mol
CAS-No.	: 75-65-0
EC-No.	: 200-889-7
Index-No.	: 603-005-00-1

Component	Classification	Concentration
<b>tert-Butanol</b>		
	Flam. Liq. 2; Acute Tox. 4; Eye Irrit. 2A; STOT SE 3; H225, H332, H319, H335, H336 Concentration limits: 20 %: STOT SE 3, H335;	<= 100 %

Millipore - 1.09629

Page 2 of 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>) Foam Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### **6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

### **6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb® ). Dispose of properly. Clean up affected area.

### **6.4 Reference to other sections**

For disposal see section 13.

---

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

#### **Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### **Hygiene measures**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

#### **Storage class**

Storage class (TRGS 510): 3: Flammable liquids

### **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Ingredients with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
tert-Butanol	75-65-0	TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen		
		TWA	100 ppm 300 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	150 ppm 450 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	100 ppm 300 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	100 ppm 300 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	150 ppm 450 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	150 ppm 450 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		PEL	100 ppm 300 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

## 8.2 Exposure controls

### Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Chloroprene  
Minimum layer thickness: 0.65 mm  
Break through time: 240 min  
Material tested: KCL 720 Camapren®

#### **Body Protection**

Flame retardant antistatic protective clothing.

#### **Respiratory protection**

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

#### **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

---

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid Color: colorless
b) Odor	camphor-like
c) Odor Threshold	ca.71 ppm
d) pH	at 20 °C (68 °F) neutral
e) Melting point/freezing point	Melting point: 24 - 25 °C (75 - 77 °F)
f) Initial boiling point and boiling range	81 - 83 °C 178 - 181 °F at 1,013 hPa
g) Flash point	15 °C (59 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 8.0 %(V) Lower explosion limit: 2.3 %(V)
k) Vapor pressure	40.7 hPa at 20 °C (68 °F)
l) Vapor density	2.56
m) Density	0.78 g/cm <sup>3</sup> at 20 °C (68 °F)
Relative density	No data available
n) Water solubility	soluble
o) Partition coefficient: n-octanol/water	log Pow: 0.30 - Bioaccumulation is not expected.
p) Autoignition temperature	470 °C (878 °F) at 1,013 hPa - see user defined free text
q) Decomposition temperature	No data available

- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties none

## 9.2 Other safety information

Dissociation constant 19.2 at 20 °C (68 °F)  
Relative vapor density 2.56

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Violent reactions possible with:

Alkali metals  
Alkaline earth metals  
Strong acids  
Aluminum  
Strong oxidizing agents

### 10.4 Conditions to avoid

Warming.

### 10.5 Incompatible materials

rubber, various plastics

### 10.6 Hazardous decomposition products

Peroxides  
In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male and female - 2,733 mg/kg  
(US-EPA)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Acute toxicity estimate Inhalation - Expert judgment - 4 h - 11.1 mg/l - vapor

Dermal: No data available

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h

(Draize Test)

**Serious eye damage/eye irritation**

Eyes - Rabbit  
(US-EPA)

**Respiratory or skin sensitization**

Sensitisation test (Magnusson and Kligman): - Guinea pig  
Result: negative  
(OECD Test Guideline 406)

**Germ cell mutagenicity**

Test Type: In vitro mammalian cell gene mutation test  
Test system: Mouse lymphoma test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Micronucleus test  
Species: Mouse  
Cell type: Red blood cells (erythrocytes)  
Application Route: Oral  
Method: OECD Test Guideline 474  
Result: negative

**Carcinogenicity**

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.  
OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**Reproductive toxicity**

No data available

**Specific target organ toxicity - single exposure**

Inhalation - May cause respiratory irritation. - Respiratory system  
Inhalation - May cause drowsiness or dizziness. - Nervous system

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**11.2 Additional Information**

drying, cracking of the skin, Skin irritation  
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence



---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - > 961 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 933 mg/l - 48 h (Directive 67/548/EEC, Annex V, C.2.)
Toxicity to algae	IC50 - Desmodesmus subspicatus (green algae) - > 1,000 mg/l - 72 h Remarks: (IUCLID)
Toxicity to bacteria	EC10 - Pseudomonas putida - 6,900 mg/l - 16 h Remarks: (External MSDS)

### 12.2 Persistence and degradability

Biodegradability	Result: > 99.9 % - Readily eliminated from water (OECD Test Guideline 302B)
------------------	--

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

Stability in water	Remarks: No data available
--------------------	----------------------------

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 1120    Class: 3    Packing group: II

Millipore - 1.09629

Page 9 of 10

Proper shipping name: Butanols  
Reportable Quantity (RQ):  
Poison Inhalation Hazard: No

**IMDG**

UN number: 1120    Class: 3    Packing group: II    EMS-No: F-E, S-D  
Proper shipping name: BUTANOLS

**IATA**

UN number: 1120    Class: 3    Packing group: II  
Proper shipping name: Butanols

---

**SECTION 15: Regulatory information**

**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

tert-Butanol	CAS-No. 75-65-0	Revision Date 2007-03-01
--------------	--------------------	-----------------------------

**Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

---

**SECTION 16: Other information**

**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 8.2    Revision Date: 01/14/2022    Print Date: 06/02/2022