

# SAFETY DATA SHEET

Version 8.8 Revision Date 02/09/2022 Print Date 06/01/2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Methanol For HPLC Gradient Analysis,

<br/>Spectrophotometry and <br/>Gas

Chromatography OmniSolv®

Product Number : MX0488
Brand : Millipore
Index-No. : 603-001-00-X
CAS-No. : 67-56-1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

# 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system,

H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements



#### Pictogram



Signal word	Danger
-------------	--------

427264	statement(s	١
Hazaro	statementis	)

H225 Highly flammable liquid and vapor.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs (Eyes, Central nervous system).

#### Precautionary statement(s)

P210	Keep away f	rom heat/	sparks/	open flames/	hot surfaces. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
Take off contaminated clothing and wash before reuse.

P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Formula : CH40

Molecular weight : 32.04 g/mol CAS-No. : 67-56-1 EC-No. : 200-659-6 Index-No. : 603-001-00-X

Component	Classification	Concentration
Methanol		
	Flam. Liq. 2; Acute Tox. 3;	<= 100 %
	STOT SE 1; H225, H301,	



H331, H311, H370	
Concentration limits:	
>= 10 %: STOT SE 1,	
H370; 3 - < 10 %: STOT	
SE 2, H371;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

#### **General advice**

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed No data available

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

# Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

#### 5.2 Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.



Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

# 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

#### **5.4** Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

#### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

#### 6.4 Reference to other sections

For disposal see section 13.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

# Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

# Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids



# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Ingredients with workplace control parameters

Ingredients wi	<u>ith workplace</u>	control pa	<u>arameters</u>			
Component	CAS-No.	Value	Control parameters	Basis		
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Danger of	f cutaneous abso	orption		
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Danger of	f cutaneous abso	` '		
		ST	250 ppm 325 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential	for dermal absor	ption		
		TWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential	for dermal absor	ption		
		TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants		
		PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		Skin				
		С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		Skin	<u>.</u>			
		STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		Skin				
		TWA	200 ppm 260 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000		
		Skin nota	tion	-		
		STEL	250 ppm 325 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000		
		Skin notation				

**Biological occupational exposure limits** 

Component	CAS-No.	Parameters	Value	Biological	Basis
				specimen	



Methanol	67-56-1	Methanol	15 mg/l		ACGIH - Biological
					Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

# 8.2 Exposure controls

### **Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

#### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

# Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

#### **Body Protection**

Flame retardant antistatic protective clothing.

#### Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

# **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.



#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

**Appearance** Form: liquid

Color: colorless

b) Odor characteristic

c) Odor Threshold 10 ppm

point/freezing point

and boiling range

d) pH No data available

Melting point: -97.8 °C (-144.0 °F) - (ECHA) e) Melting

Initial boiling point 64.7 °C 148.5 °F at 1,013 hPa - (ECHA) f)

g) Flash point 9.7 °C (49.5 °F) - closed cup - Regulation (EC) No. 440/2008,

Annex, A.9

6.3 - Diethyl ether1.9 - n-butyl acetate h) Evaporation rate

i) Flammability (solid, No data available gas)

j) Upper/lower flammability or

Upper explosion limit: 44 %(V) Lower explosion limit: 5.5 %(V) explosive limits

k) Vapor pressure 169.27 hPa at 25 °C (77 °F)

Vapor density 1.11

m) Density 0.79 g/cm3 at 20 °C (68 °F)

Relative density 0.79 - 0.820 °C

1,000 g/l at 20 °C (68 °F) - completely misciblesoluble n) Water solubility o) Partition coefficient: log Pow: -0.77 - (Lit.), Bioaccumulation is not expected.

n-octanol/water

temperature

455.0 °C (851.0 °F) at 1,013 hPa - DIN 51794 p) Autoignition

q) Decomposition Distillable in an undecomposed state at normal pressure. temperature

0.54 - 0.59 mm2/s at 20 °C (68 °F) r) Viscosity

No data available s) Explosive properties

t) Oxidizing properties none

#### 9.2 Other safety information

Minimum ignition

energy

0.14 mJ

Conductivity  $< 1 \mu S/cm$ 

Relative vapor 1.11

density



#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Vapors may form explosive mixture with air. Vapors may form explosive mixture with air.

#### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature). The product is chemically stable under standard ambient conditions (room temperature).

# 10.3 Possibility of hazardous reactions

Risk of explosion with:

Oxidizing agents

perchloric acid

perchlorates

salts of oxyhalogenic acids

chromium(VI) oxide

halogen oxides

nitrogen oxides

nonmetallic oxides

chromosulfuric acid

chlorates

hydrides

zinc diethyl

halogens

powdered magnesium

hydrogen peroxide

Nitric acid

sulfuric acid

permanganic acid

sodium hypochlorite

Exothermic reaction with:

acid halides

Acid anhydrides

Reducing agents

acids

**Bromine** 

Chlorine

Chloroform

magnesium

tetrachloromethane

Risk of ignition or formation of inflammable gases or vapours with:

Fluorine

Oxides of phosphorus

Raney-nickel

Generates dangerous gases or fumes in contact with:

Alkaline earth metals

Alkali metals

#### 10.4 Conditions to avoid

Warming.

Warming.

#### 10.5 Incompatible materials

various plastics, magnesium, zinc alloys

# 10.6 Hazardous decomposition products

In the event of fire: see section 5

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Drying-out effect resulting in rough and chapped skin.

# Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

# Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

#### Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

# Carcinogenicity

Did not show carcinogenic effects in animal experiments.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

Based on available data the classification criteria are not met.

# Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

# Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

#### 11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis

drop in blood pressure

agitation, spasms

inebriation

Dizziness

Drowsiness

Headache

Impairment of vision

Blindness

narcosis

Coma

Symptoms may be delayed.

Damage to:

Liver

Kidney

Cardiac

Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15,400.0

mg/l - 96 h (US-EPA)

Toxicity to daphnia

semi-static test EC50 - Daphnia magna (Water flea) - 18,260 mg/l -

and other aquatic

96 h

invertebrates

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca.

22,000.0 mg/l - 96 h

(OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability Result: 99 % - Readily biodegradable.

(OECD Test Guideline 301D)

Biochemical Oxygen

600 - 1,120 mg/g

Demand (BOD)

Remarks: (IUCLID)

Chemical Oxygen

1,420 mg/g

Demand (COD)

Remarks: (IUCLID)

Theoretical oxygen demand

1,500 mg/g Remarks: (Lit.)

Ratio BOD/ThBOD

76 %

Remarks: Closed Bottle test(IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d

at 20 °C - 5 mg/l(Methanol)

Bioconcentration factor (BCF): 1.0

12.4 Mobility in soil

Will not adsorb on soil.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Additional ecological Avoid release to the environment.

information

Stability in water at 19 °C83 - 91 % - 72 h

Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

# **SECTION 14: Transport information**

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: Methanol Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No

**IMDG** 

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOL

**IATA** 

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: Methanol

# **SECTION 15: Regulatory information**

## **SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

#### **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol CAS-No. Revision Date 67-56-1 2007-07-01

#### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

#### **SECTION 16: Other information**

#### **Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See

Millipore - MX0488

Millipore SigMa www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.8 Revision Date: 02/09/2022 Print Date: 06/01/2022

