

**TANTALUM(V) ISOPROPOXIDE****Safety Data Sheet AKT813**

Date of issue: 01/15/2016

Revision date: 04/04/2017

Version: 2.0

SECTION 1: Identification**1.1. Identification**

Product name	: TANTALUM(V) ISOPROPOXIDE
Product code	: AKT813
Product form	: Substance
Physical state	: Solid
Formula	: C ₁₅ H ₃₅ O ₅ Ta
Synonyms	: PENTAIISOPROPOXYTANTALUM
Chemical family	: METAL ESTER

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier**GELEST, INC.**

11 East Steel Road
Morrisville, PA 19067
USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable solids Category 2	H228 Flammable solid
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Full text of H statements : see section 16	

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H228 - Flammable solid
H315 - Causes skin irritation
H319 - Causes serious eye irritation

Precautionary statements (GHS US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, open flames, sparks. - No smoking.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P264 - Wash hands thoroughly after handling.
P302+P352 - If on skin: Wash with plenty of soap and water
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention.
P321 - Specific treatment (see first aid instructions on this label)
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use water spray, alcohol resistant foam, carbon dioxide, dry chemical to extinguish.

2.3. Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification

: Additional isopropanol may be formed by reaction with moisture and water. The US ACGIH (TWA) for isopropanol is 200 ppm. The US OSHA PEL (TWA) for isopropanol is 400 ppm.

2.4. Unknown acute toxicity (GHS US)

Not applicable

TANTALUM(V) ISOPROPOXIDE

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : TANTALUM(V) ISOPROPOXIDE
CAS-No. : 16761-83-4

Name	Product identifier	%	GHS-US classification
Tantalum(V) isopropoxide	(CAS-No.) 16761-83-4	95 - 100	Flam. Sol. 2, H228 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Alcohol-resistant foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable solid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid contact with skin and eyes. Do not breathe dust.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

TANTALUM(V) ISOPROPOXIDE

Safety Data Sheet

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Ground/bond container and receiving equipment. Use only non-sparking tools. Provide local exhaust or general room ventilation to minimize exposure to dust.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep in a cool place.

Incompatible materials : Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tantalum(V) isopropoxide (16761-83-4)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ tantalum

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified dust and mist (orange cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Solid.

Molecular mass : 476.39 g/mol

Color : Pale yellow.

Odor : Mild.

Odor threshold : No data available

Refractive index : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : 92 °C

Freezing point : No data available

Boiling point : 122 °C @ 0.1 mm Hg

Flash point : > 65 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

TANTALUM(V) ISOPROPOXIDE

Safety Data Sheet

Flammability (solid, gas)	: Flammable solid
Vapor pressure	: 8 mm Hg @ 20 °C
Relative vapor density at 20 °C	: > 1
Relative density	: 1.31
% Volatiles	: > 50 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water liberating isopropanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Isopropanol. Organic acid vapors. Tantalum oxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

TANTALUM(V) ISOPROPOXIDE (16761-83-4)

Toxicity information	8000 mg/kg oral rat, LD50; Note: The hydrolysis products of tantalum isopropoxide are tantalum oxide and isopropanol. Tantalum oxide is reported to be moderately toxic.
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Material generates isopropanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

TANTALUM(V) ISOPROPOXIDE

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1325
DOT NA no. : UN1325

14.2. UN proper shipping name

Transport document description : UN1325 Flammable solids, organic, n.o.s. (TANTALUM(V) ISOPROPOXIDE), 4.1, III
Proper Shipping Name (DOT) : Flammable solids, organic, n.o.s.
(TANTALUM(V) ISOPROPOXIDE)
Class (DOT) : 4.1 - Class 4.1 - Flammable Solid 49 CFR 173.124
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 4.1 - Flammable solid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 213
DOT Packaging Bulk (49 CFR 173.xxx) : 240
DOT Packaging Exceptions (49 CFR 173.xxx) : 151
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 133
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 25 kg
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 100 kg
CFR 175.75)

TANTALUM(V) ISOPROPOXIDE

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

TANTALUM(V) ISOPROPOXIDE (16761-83-4)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Tantalum(V) isopropoxide (16761-83-4)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases::

H228	Flammable solid
H315	Causes skin irritation
H319	Causes serious eye irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)
Physical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/15/2016

Revision date: 04/04/2017

Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

TANTALUM(V) ISOPROPOXIDE

Safety Data Sheet

© 2019 Gelest Inc. Morrisville, PA 19067

