

# **SAFETY DATA SHEET**

Creation Date 16-Sep-2014 Revision Date 23-Feb-2022 Revision Number 3

1. Identification

Product Name 2-Ethylhexyl acrylate, stabilized

Cat No. : L03854

**CAS No** 103-11-7

Synonyms 2-Ethylhexyl-2-propenoate; Acrylic acid, 2-ethylhexyl ester.; Octyl acrylate

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

## Details of the supplier of the safety data sheet

### Company

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

**Emergency Telephone Number** 

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

## 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin Sensitization

Category 2

Category 2

Category 2

Skin Sensitization

Category 1

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system.

### Label Elements

### Signal Word

Warning

#### **Hazard Statements**

Combustible liquid
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation



## **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep cool

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

#### **Eves**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### **Storage**

Store in a well-ventilated place. Keep container tightly closed

Store locked up

### **Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Cancer - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
2-Ethylhexyl acrylate	103-11-7	>95
4-Methoxyphenol	150-76-5	0.001-0.002

### 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest

pain, muscle pain or flushing

Notes to Physician Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

**Flash Point** 86 °C / 186.8 °F

Method - No information available

Autoignition Temperature 245 °C / 473 °F

**Explosion Limits** 

 Upper
 6.4 vol %

 Lower
 0.8 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Combustible material. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2).

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>

HealthFlammabilityInstabilityPhysical hazards221N/A

## 6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Remove all

sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions**Should not be released into the environment. Do not flush into surface water or sanitary

sewer system.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** Remove all sources of ignition.

## 7. Handling and storage

**Handling** Wear personal protective equipment/face protection. Avoid ingestion and inhalation. Ensure

adequate ventilation. Do not get in eyes, on skin, or on clothing. Keep away from open

flames, hot surfaces and sources of ignition.

Storage.

Keep in a dry place. Keep container tightly closed. Keep away from heat, sparks and flame. Protect from direct sunlight. Keep refrigerated. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Bases. Strong acids. Amines. Halogens. Peroxides.

## 8. Exposure controls / personal protection

## **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
4-Methoxyphenol	TWA: 5 mg/m <sup>3</sup>	(Vacated) TWA: 5 mg/m <sup>3</sup>	acated) TWA: 5 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

**Eye/face Protection**Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorpungent

Odor Threshold No information available No information available

Melting Point/Range -90 °C / -130 °F

**Boiling Point/Range** 215 - 219 °C / 419 - 426.2 °F @ 760 mmHg

Flash Point 86 °C / 186.8 °F
Evaporation Rate No information available

Flammability (solid,gas)
Not applicable
Flammability or explosive limits

Upper 6.4 vol % bower 0.8 vol %

 Vapor Pressure
 0.13 mbar @ 20 °C

 Vapor Density
 6.35 (Air = 1.0)

Specific Gravity 0.880

SolubilityInsoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature245 °C / 473 °FDecomposition TemperatureNo information available

**Viscosity** 1.7 mPa.s at 20 °C

**Molecular Formula** C11 H20 O2 Molecular Weight 184.28

## 10. Stability and reactivity

None known, based on information available **Reactive Hazard** 

Stability Light sensitive. heat sensitive.

**Conditions to Avoid** Incompatible products. Exposure to light. To avoid thermal decomposition, do not overheat.

Keep away from open flames, hot surfaces and sources of ignition.

Bases, Strong acids, Amines, Halogens, Peroxides **Incompatible Materials** 

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

**Hazardous Polymerization** Hazardous polymerization may occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

#### **Acute Toxicity**

#### **Product Information**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Ethylhexyl acrylate	LD50 = 4435 mg/kg (Rat)	LD50 = 7522 mg/kg ( Rabbit )	LC50 > 1.19 mg/L (Rat) 8 h
4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	Not listed

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to respiratory system and skin May cause eye irritation

Sensitization May cause sensitization by skin contact

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
2-Ethylhexyl acrylate	103-11-7	Group 2B	Not listed	Not listed	X	Not listed
4-Methoxyphenol	150-76-5	Not listed				

**Mutagenic Effects** Not mutagenic in AMES Test

**Reproductive Effects** No information available.

No information available. **Developmental Effects** 

No information available. **Teratogenicity** 

Respiratory system STOT - single exposure STOT - repeated exposure None known

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

### **Ecotoxicity**

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
2-Ethylhexyl acrylate	EC50: = 47 mg/L, 96h (Desmodesmus subspicatus) EC50: = 44 mg/L, 72h (Desmodesmus subspicatus)	LC50: = 1.81 mg/L, 96h semi-static (Oncorhynchus mykiss)	EC50 > 10000 mg/L 30 min	EC50: = 17.45 mg/L, 48h (Daphnia magna)
4-Methoxyphenol	Not listed	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 3.66 mg/L 5 min EC50 = 4.30 mg/L 15 min EC50 = 4.61 mg/L 30 min	Not listed

Persistence and Degradability May persist

Bioaccumulation/ Accumulation No information available.

**Mobility** . Is not likely mobile in the environment due its low water solubility.

Component	log Pow
2-Ethylhexyl acrylate	4.64
4-Methoxyphenol	1.3

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

**DOT** 

UN-No UN3334

Proper Shipping Name AVIATION REGULATED LIQUID, N.O.S.

Hazard Class

**TDG** 

UN-No UN3334

Proper Shipping Name AVIATION REGULATED LIQUID, N.O.S.

Hazard Class

<u>IATA</u>

UN-No UN3334

Proper Shipping Name AVIATION REGULATED LIQUID, N.O.S.\*

Hazard Class 9

IMDG/IMO Not regulated

## 15. Regulatory information

**United States of America Inventory** 

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
2-Ethylhexyl acrylate	103-11-7	Χ	ACTIVE	-
4-Methoxyphenol	150-76-5	Χ	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
2-Ethylhexyl acrylate	103-11-7	Х	-	203-080-7	Χ	Χ	Χ	Χ	Х	KE-29533
4-Methoxyphenol	150-76-5	Х	-	205-769-8	Х	Χ	Χ	Х	Х	KE-23353

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

## **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
2-Ethylhexyl acrylate	103-11-7	Carcinogen	-	Carcinogen

# U.S. State Right-to-Know

## Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
2-Ethylhexyl acrylate	X	X	X	-	X
4-Methoxyphenol	X	X	X	-	Х

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

## U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

### Other International Regulations

Mexico - Grade No information available

## Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
2-Ethylhexyl acrylate	-	Use restricted. See item 75. (see link for restriction details)	-
4-Methoxyphenol	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

## Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
2-Ethylhexyl acrylate	103-11-7	Listed	Not applicable	Not applicable	Not applicable
4-Methoxyphenol	150-76-5	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
2-Ethylhexyl acrylate	103-11-7	Not applicable	Not applicable	Not applicable	Not applicable
4-Methoxyphenol	150-76-5	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information
-----------------------

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com www.alfa.com

 Creation Date
 16-Sep-2014

 Revision Date
 23-Feb-2022

 Print Date
 23-Feb-2022

**Revision Summary** SDS authoring systems update, replaces ChemGes SDS No. 103-11-7/2.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**