

SAFETY DATA SHEET

Revision Date 23-Feb-2022 Revision Number 3

1. Identification

Product Name Methyl acrylate

Cat No. : A13128

CAS No 96-33-3

Synonyms Methyl 2-propenoate

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

Emergency Telephone Number

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

	_
Flammable liquids	Category 2
Acute oral toxicity	Category 4
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity - Dusts and Mists	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Toxic if inhaled
May cause respiratory irritation
Harmful if swallowed or in contact with skin



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Contaminated work clothing should not be allowed out of the workplace

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Indestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

Other hazards

Stench.

WARNING. Cancer - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl acrylate	96-33-3	>95
4-Methoxyphenol	150-76-5	0.001-0.002

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Get medical attention. Wash off immediately with plenty of water for at least 15 minutes.

Inhalation Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Get medical attention.

Most important symptoms and

effects

Difficulty in breathing. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle

pain or flushing

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray. Carbon dioxide (CO 2). Dry chemical. Chemical foam. Water mist may be used

to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point -3 °C / 26.6 °F

Method - No information available

Autoignition Temperature 463 °C / 865.4 °F

Explosion Limits

Upper 25% **Lower** 2.8%

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

Revision Date 23-Feb-2022 Methyl acrylate

6. Accidental release measures

Personal Precautions Environmental Precautions Remove all sources of ignition. Take precautionary measures against static discharges. Do not flush into surface water or sanitary sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Prevent product from entering drains. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not flush into surface water or sanitary sewer system.

7. Handling and storage

Handling

Avoid contact with skin and eyes. Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Keep in a dry place. Keep container tightly closed. Refrigerator/flammables. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Acids. Bases. Peroxides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl acrylate	TWA: 2 ppm	(Vacated) TWA: 10 ppm	IDLH: 250 ppm	TWA: 2 ppm
	Skin	(Vacated) TWA: 35 mg/m ³	TWA: 10 ppm	
		Skin	TWA: 35 mg/m ³	
		TWA: 10 ppm	_	
		TWA: 35 mg/m ³		
4-Methoxyphenol	TWA: 5 mg/m ³	(Vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eveglasses or chemical safety googles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection**

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorStench

Odor ThresholdNo information availablepHNo information available

Melting Point/Range -75 °C / -103 °F

Boiling Point/Range

80 °C / 176 °F @ 760 mmHg
Flash Point

-3 °C / 26.6 °F

Evaporation Rate

80 °C / 176 °F @ 760 mmHg

-3 °C / 26.6 °F

No information available

Flammability (solid,gas)

Not applicable

Flammability or explosive limits

 Upper
 25%

 Lower
 2.8%

Vapor PressureNo information availableVapor DensityNo information available

Specific Gravity 0.956

Solubility
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity

No information available
463 °C / 865.4 °F
No information available
No information available

Viscosity

Molecular Formula

Molecular Weight

No informatio
C4 H6 O2
86.09

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Light sensitive. Hazardous polymerization does not occur. Hazardous polymerization may

occur upon depletion of inhibitor.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure

to light. Incompatible products.

Incompatible Materials Acids, Bases, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization may occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

	Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ſ	Methyl acrylate	LD50 = 277 mg/kg (Rat)	LD50 = 1243 mg/kg (Rabbit)	LC50 = 3.58 mg/L (Rat) 4 h
				, ,
ſ	4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	Not listed
		3 3 4		

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Revision Date 23-Feb-2022 Methyl acrylate

Sensitization May cause sensitization by skin contact

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl acrylate	96-33-3	Group 2B	Not listed	Not listed	X	Not listed
4-Methoxyphenol	150-76-5	Not listed				

No information available **Mutagenic Effects**

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest

pain, muscle pain or flushing

No information available **Endocrine Disruptor Information**

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl acrylate	EC50: <= 46.78 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 15 mg/L, 72h (Desmodesmus subspicatus)	LC50: = 1.81 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: = 2.11 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 260 mg/L 17 h	EC50: = 2.2 mg/L, 48h (Daphnia magna)
4-Methoxyphenol	Not listed	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 3.66 mg/L 5 min EC50 = 4.30 mg/L 15 min EC50 = 4.61 mg/L 30 min	Not listed

Persistence is unlikely based on information available. **Persistence and Degradability**

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl acrylate	0.739
4-Methoxyphenol	1.3

13. Disposal considerations

Chemical waste generators must determine whether a discarded chemical is classified as a **Waste Disposal Methods**

hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1919

Proper Shipping Name METHYL ACRYLATE, STABILIZED

Hazard Class 3
Packing Group ||

_ TDG

UN-No UN1919

Proper Shipping Name METHYL ACRYLATE, STABILIZED

Hazard Class 3 Packing Group II

<u>IATA</u>

UN-No UN1919

Proper Shipping Name METHYL ACRYLATE, STABILIZED

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1919

Proper Shipping Name METHYL ACRYLATE, STABILIZED

Hazard Class 3
Packing Group ||

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl acrylate	96-33-3	X	ACTIVE	-
4-Methoxyphenol	150-76-5	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl acrylate	96-33-3	Χ	-	202-500-6	Χ	Χ	Χ	Χ	Χ	KE-29592
4-Methoxyphenol	150-76-5	Х	-	205-769-8	Χ	Χ	Х	Х	Х	KE-23353

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl acrylate	96-33-3	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Methyl acrylate	96-33-3	Carcinogen	-	Carcinogen

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl acrylate	X	X	X	-	X
4-Methoxyphenol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

	Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Ī	Methyl acrylate	-	Use restricted. See item 75.	-
			(see link for restriction details)	
Ī	4-Methoxyphenol	=	Use restricted. See item 75.	-
-			(see link for restriction details)	

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl acrylate	96-33-3	Listed	Not applicable	Not applicable	Not applicable
4-Methoxyphenol	150-76-5	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
	Qualifying Quantities Qualifying Quantities				
		for Major Accident	for Safety Report		
		Notification	Requirements		

	Methyl acrylate	96-33-3	500 tonne	2000 tonne	Not applicable	Not applicable
Ī	4-Methoxyphenol	150-76-5	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

Revision Date 23-Feb-2022 Print Date 23-Feb-2022

Revision Summary SDS authoring systems update, replaces ChemGes SDS No. 96-33-3.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS