

SAFETY DATA SHEET

Version 6.7
Revision Date 02/14/2022
Print Date 05/28/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Ethylenediamine

Product Number : 391085

Brand : Aldrich

Index-No. : 612-006-00-6

CAS-No. : 107-15-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 3), H311

Skin corrosion (Category 1B), H314

Serious eye damage (Category 1), H318

Respiratory sensitization (Sub-category 1B), H334

Skin sensitization (Sub-category 1B), H317

Short-term (acute) aquatic hazard (Category 3), H402

Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H226	Flammable liquid and vapor.
H302 + H332	Harmful if swallowed or if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Rapidly absorbed through skin.
Lachrymator.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : 1,2-Diaminoethane

Formula : C₂H₈N₂

Molecular weight : 60.10 g/mol

CAS-No. : 107-15-3

EC-No. : 203-468-6

Index-No. : 612-006-00-6

Component	Classification	Concentration
ethylenediamine		
	Flam. Liq. 3; Acute Tox. 4; Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; Resp. Sens. 1B; Skin Sens. 1B; Aquatic Acute 3; Aquatic Chronic 3; H226, H302, H332, H311, H314, H318, H334, H317, H402, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NO_x)

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Air and moisture sensitive. Handle and store under inert gas.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethylenediamine	107-15-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen Danger of cutaneous absorption		

		TWA	10 ppm 25 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	10 ppm 25 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	10 ppm 25 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		PEL	10 ppm 25 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm

Break through time: 240 min

Material tested: KCL 720 Camapren®

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless
b) Odor	amine-like
c) Odor Threshold	No data available
d) pH	12.2 at 100 g/l at 20 °C (68 °F)
e) Melting point/freezing point	Melting point/range: 8.5 °C (47.3 °F) - lit.
f) Initial boiling point and boiling range	118 °C 244 °F - lit.
g) Flash point	38 °C (100 °F) - closed cup - DIN 51755 Part 1
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 17 %(V) Lower explosion limit: 2 %(V)
k) Vapor pressure	12 hPa at 20 °C (68 °F)
l) Vapor density	2.07 - (Air = 1.0)
m) Density	0.899 g/mL at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	1,000 g/l - miscible
o) Partition coefficient: n-octanol/water	log Pow: -2.04 - Bioaccumulation is not expected., (Lit.)
p) Autoignition temperature	405 °C (761 °F) - DIN 51794
q) Decomposition temperature	> 120 °C (> 248 °F) -
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none

9.2 Other safety information

Relative vapor density	2.07 - (Air = 1.0)
------------------------	--------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

acid halides

perchlorates

Acrolein

Halogenated hydrocarbon

Acid chlorides

Alcohols

Aldehydes

phosphorus halides

Exothermic reaction with:

chlorosulfonic acid

Hydrogen chloride gas

acetic acid

Acetic anhydride

fuming sulfuric acid

Oxidizing agents

acryl aldehyde

acids

carbon disulfide

silver perchlorate

vinyl acetate

acrylic acid

1-chloro-2,3-epoxypropane

Risk of explosion with:

Nitromethane

with

Tetryl (N-Methyl-N-2,4,6-tetranitroaniline)

nitric acid (conc.)

Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines!

10.4 Conditions to avoid

Air Exposure to moisture.

Heating.

10.5 Incompatible materials

Aluminum, Lead, magnesium, Zinc, zinc alloys, Copper, Copper alloys, Iron, brass, bronze

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 866 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male - 4 h - 14.7 mg/l - vapor

Remarks: (ECHA)

LD50 Dermal - Rabbit - male - 560 mg/kg

Remarks: (ECHA)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Corrosive - 15 min

Remarks: (ECHA)

Causes poorly healing wounds.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Corrosive

Remarks: (ECHA)

Causes serious eye damage.

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: positive

Remarks: (ECHA)

(Regulation (EC) No 1272/2008, Annex VI)

(Regulation (EC) No 1272/2008, Annex VI)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: unscheduled DNA synthesis assay

Test system: rat hepatocytes

Metabolic activation: without metabolic activation

Result: negative

Remarks: (ECHA)

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Remarks: (ECHA)

Test Type: dominant lethal test

Species: Rat

Application Route: Oral

Result: negative

Remarks: (ECHA)

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Mouse - male - Dermal - NOAEL (No observed adverse effect level) - 8.3 mg/kg

Remarks: (ECHA)

Repeated dose toxicity - Rat - male and female - inhalation (vapor) - 6 Weeks - NOAEL (No observed adverse effect level) - 48 mg/kg - LOAEL (Lowest observed adverse effect level) - 107 mg/kg

Remarks: (ECHA)

Repeated dose toxicity - Rat - male and female - Oral - 3 Months - NOAEL (No observed adverse effect level) - 22 mg/kg - LOAEL (Lowest observed adverse effect level) - 114 mg/kg

RTECS: KH8575000

Vomiting, Diarrhea, Abdominal pain

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	semi-static test LC50 - <i>Poecilia reticulata</i> (guppy) - 640 mg/l - 96 h (Directive 67/548/EEC, Annex V, C.1.) Remarks: (ECHA)
	semi-static test NOEC - <i>Gasterosteus aculeatus</i> (threespine stickleback) - > 10 mg/l - 28 d Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - <i>Daphnia magna</i> (Water flea) - 16.7 mg/l - 48 h (Directive 67/548/EEC, Annex V, C.2.) Remarks: (ECHA)
	semi-static test NOEC - <i>Daphnia magna</i> (Water flea) - 0.16 mg/l - 21 d Remarks: (ECHA)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> (algae) - 645 mg/l - 72 h (Directive 67/548/EEC, Annex V, C.3.)
Toxicity to bacteria	static test EC50 - Bacteria - 3.2 mg/l - 2 h Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 95 % - Readily biodegradable. (Regulation (EC) No. 440/2008, Annex, C.4-E)
------------------	---

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1604 Class: 8 (3) Packing group: II
Proper shipping name: Ethylenediamine
Reportable Quantity (RQ): 5000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1604 Class: 8 (3) Packing group: II EMS-No: F-E, S-C
Proper shipping name: ETHYLENEDIAMINE

IATA

UN number: 1604 Class: 8 (3) Packing group: II
Proper shipping name: Ethylenediamine

SECTION 15: Regulatory information

SARA 302 Components

ethylenediamine

CAS-No.
107-15-3

Revision Date
2007-07-01

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See

www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.7

Revision Date: 02/14/2022

Print Date: 05/28/2022