

SAFETY DATA SHEET

Version 6.14 Revision Date 09/13/2021 Print Date 05/28/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifiers**

Product name : Chromium(VI) oxide

Product Number : 236470 Brand : SIGALD

: 024-001-00-0 Index-No. CAS-No. : 1333-82-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 **UNITED STATES**

Telephone : +1 314 771-5765 : +1 800 325-5052

Emergency telephone

Fax

800-424-9300 CHEMTREC (USA) +1-703-Emergency Phone #

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Oxidizing solids (Category 1), H271

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 2), H330

Acute toxicity, Dermal (Category 3), H311

Skin corrosion (Category 1A), H314

Serious eye damage (Category 1), H318

Respiratory sensitization (Category 1), H334

Skin sensitization (Category 1), H317

Germ cell mutagenicity (Category 1B), H340

Carcinogenicity (Category 1A), H350

Reproductive toxicity (Category 2), H361

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335



Specific target organ toxicity - repeated exposure, Inhalation (Category 1), H372 Short-term (acute) aquatic hazard (Category 1), H400 Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram	
Signal word	Danger
Hazard statement(s) H271 H301 + H311 H314 H317 H330 H334	May cause fire or explosion; strong oxidizer. Toxic if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficulties
H335 H340 H350 H361 H372	if inhaled. May cause respiratory irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated
H410	exposure if inhaled. Very toxic to aquatic life with long lasting effects.
Precautionary statement(s) P201 P202 P210 P220 P221 P260	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat. Keep/Store away from clothing/ combustible materials. Take any precaution to avoid mixing with combustibles. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 P270 P271 P272	Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace.
P273 P280 P283 P284	Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. Wear fire/ flame resistant/ retardant clothing. Wear respiratory protection.
P301 + P310 + P330 P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated
P304 + P340 + P310 P305 + P351 + P338 + P310	clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing. Immediately call a POISON CENTER/ doctor.



P306 + P360	IF ON CLOTHING: rinse immediately contaminated clothing and skin with plenty of water before removing clothes.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P371 + P380 + P375	In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Chromic anhydride

Formula : CrO₃ Molecular weight : 99.99

Molecular weight : 99.99 g/mol CAS-No. : 1333-82-0 EC-No. : 215-607-8 Index-No. : 024-001-00-0

Component	Classification	Concentration
chromium trioxide		
	Ox. Sol. 1; Acute Tox. 3; Acute Tox. 2; Acute Tox. 3; Skin Corr. 1A; Eye Dam. 1; Resp. Sens. 1; Skin Sens. 1; Muta. 1B; Carc. 1A; Repr. 2; STOT SE 3; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H271, H301, H330, H311, H314, H318, H334, H317, H340, H350, H361, H335, H372, H400, H410 Concentration limits: >= 1 %: STOT SE 3, H335; M-Factor - Aquatic Acute: 10	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.



SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sandUse extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given. For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Chromium oxides

Not combustible.

Has a fire-promoting effect due to release of oxygen.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SIGALD - 236470

Millipore

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep locked up or in an area accessible only to qualified or authorized persons. Separately or together with other oxidising substances only and away from sources of ignition and heat. Because of their oxidation potential these products can raise the burning rate of combustible substances substantially or ignite combustible substances on contact with them.

hygroscopic Heat sensitive.

Storage class

Storage class (TRGS 510): 5.1A: Strongly oxidizing hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Ingredients with	Trigredients with workplace control parameters						
Component	CAS-No.	Value	Control	Basis			
			parameters				
chromium trioxide	1333-82-0	TWA	0.0002	USA. ACGIH Threshold Limit			
			mg/m3	Values (TLV)			
	Remarks	Dermal Sensitization					
		Respiratory sensitization					
		Confirmed human carcinogen					
		Danger of cutaneous absorption					
		STEL	0.0005	USA. ACGIH Threshold Limit			
			mg/m3	Values (TLV)			
		Dermal Ser	nsitization				
		Respiratory	sensitization				
		Confirmed human carcinogen					
		Danger of cutaneous absorption					
		PEL	0.005 mg/m3	OSHA Specifically Regulated			
				Chemicals/Carcinogens			
		OSHA specifically regulated carcinogen					
		TWA	0.0002	USA. NIOSH Recommended			
			mg/m3	Exposure Limits			
		Potential Occupational Carcinogen					
		PEL	0.005 mg/m3	California permissible exposure			
				limits for chemical			
				contaminants (Title 8, Article			
				107)			
		С	0.1 mg/m3	California permissible exposure			
				limits for chemical			
				contaminants (Title 8, Article			
				107)			

Biological occupational exposure limits

biological occupational exposure innits						
Component	CAS-No.	Parameters	Value	Biological specimen	Basis	
chromium trioxide	1333-82-0	Total chromium	25 μg/l	Urine	ACGIH - Biological Exposure Indices (BEI)	
	Remarks	End of shift at end of workweek				
		Total chromium	10 µg/l	Urine	ACGIH - Biological Exposure Indices (BEI)	
		Increase during shift				

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.



Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Body Protection

Acid-resistant protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

1 Information on basic physical and chemical properties

a) Appearance Form: crystalline

Color: dark red

b) Odor odorless

c) Odor Threshold Not applicable

d) pH < 1 at 100 g/l at 20 °C (68 °F)

e) Melting point/range: 196 °C (385 °F) - dec.

point/freezing point

f) Initial boiling point No data available

and boiling range



g) Flash point ()Not applicableh) Evaporation rate No data available

) Flammability (solid, The product is not flammable. - Test N.1: Test method for

gas) readily combustible solids

flammability or explosive limits

k) Vapor pressure Not applicable

k) Vapor pressure Not applicablel) Vapor density Not applicable

m) Density 2.7 g/cm3 at 20 °C (68 °F)

Relative density ca.2.7 - OECD Test Guideline 109

No data available

n) Water solubility ca.1,667 g/l - Regulation (EC) No. 440/2008, Annex, A.6 -

soluble

o) Partition coefficient: Not applicable for inorganic substances

n-octanol/water

Upper/lower

j)

p) Autoignition not auto-flammable temperature

q) Decomposition above melting point temperature

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties The substance or mixture is classified as oxidizing with the

category 1. May cause fire or explosion; strong oxidizer.

9.2 Other safety information

Relative vapor Not applicable density

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Risk of explosion with:

organic combustible substances

Alkali metals

Ammonia

nonmetals

halogen-halogen compounds hydrazine and derivatives

nitrates

Reducing agents

Nitric acid



10.4 Conditions to avoid

no information available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 52 mg/kg

(OECD Test Guideline 401)

Acute toxicity estimate Inhalation - 0.051 mg/l

(Expert judgment)

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Skin corrosion/irritation

Skin - Rabbit

Result: Corrosive - 0.5 h

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes burns. Remarks: (ECHA)

Causes serious eye damage.

Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Patch test: - Human Result: positive Remarks: (IUCLID)

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Test Type: Ames test Result: positive Remarks: (IUCLID)

Carcinogenicity

Carcinogenicity - Carcinogenic in animal experiments. (Lit.)

May cause cancer. Positive evidence from human epidemiological studies.

IARC: 1 - Group 1: Carcinogenic to humans (chromium trioxide)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

Inhalation - Causes damage to organs through prolonged or repeated exposure. Aspiration hazard

No data available

11.2 Additional Information

RTECS: GB6650000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

LC50 - Pimephales promelas (fathead minnow) - 33.2 mg/l - 96 h Toxicity to fish

Remarks: (in analogy to similar products)

(ECHA)

Toxicity to daphnia

EC50 - Daphnia magna (Water flea) - 0.035 mg/l - 48 h

and other aquatic invertebrates

Remarks: (ECHA)

12.2 Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned

SIGALD - 236470

Page 10 of 12



containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1463 Class: 5.1 (6.1, 8) Packing group: II Proper shipping name: Chromium trioxide, anhydrous

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 1463 Class: 5.1 (6.1, 8) Packing group: II EMS-No: F-A, S-Q

Proper shipping name: CHROMIUM TRIOXIDE, ANHYDROUS

Marine pollutant : yes

IATA

UN number: 1463 Class: 5.1 (6.1, 8) Packing group: II

Proper shipping name: Chromium trioxide, anhydrous

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date chromium trioxide 1333-82-0 1993-04-24

SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.



SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.14 Revision Date: 09/13/2021 Print Date: 05/28/2022

