

SAFETY DATA SHEET

Revision Date 28-Feb-2020 Revision Number 3

1. Identification

Product Name tert-Butyllithium, nominally 1.5M in n-pentane

Cat No.: 44125

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Alfa Aesar Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

Emergency Telephone Number

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 1

Substances/mixtures which, in contact with water, emit Category 1

flammable gases

Pyrophoric liquids Category 1
Skin Corrosion/Irritation Category 1
Serious Eye Damage/Eye Irritation Category 1
Specific target organ toxicity (single exposure) Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Aspiration Toxicity Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

Catches fire spontaneously if exposed to air

May be fatal if swallowed and enters airways

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness or dizziness



Precautionary Statements

Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Do not allow contact with air

Keep away from any possible contact with water, because of violent reaction and possible flash fire

Handle under inert gas. Protect from moisture

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN: Immerse in cool water/wrap with wet bandages

Brush off loose particles from skin. Immerse in cool water/wrap with wet bandages

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing **Ingestion**

Do NOT induce vomiting

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store contents under inert gas

Store in a dry place. Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

Reacts violently with water

3. Composition/Information on Ingredients

| Component | CAS-No | Weight % |
|-------------------------------|----------|----------|
| Pentane | 109-66-0 | 84.65 |
| Lithium, (1,1-dimethylethyl)- | 594-19-4 | 15.35 |

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Inhalation If not breathing, give artificial respiration, Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

aspiration).

Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Most important symptoms and

effects

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Dry sand. Carbon dioxide (CO2). Powder. Do not use water or foam. CO2, dry chemical,

dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point -49 °C / -56.2 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Extremely flammable. Containers may explode when heated. Vapors may form explosive

mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). Lithium oxide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability Physical hazards W 3 2

Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

αU

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal, Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Corrosives area. Keep away from water or moist air. Keep containers tightly closed in a dry. cool and well-ventilated place. Keep away from heat, sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH | Mexico OEL (TWA) |
|-----------|---------------|---------------------------------------|---------------------------------|------------------|
| Pentane | TWA: 1000 ppm | (Vacated) TWA: 600 ppm | IDLH: 1500 ppm | TWA: 600 ppm |
| | | (Vacated) TWA: 1800 mg/m ³ | TWA: 120 ppm | |
| | | (Vacated) STEL: 750 ppm | TWA: 350 mg/m ³ | |
| | | (Vacated) STEL: 2250 | Ceiling: 610 ppm | |
| | | mg/m³ | Ceiling: 1800 mg/m ³ | |
| | | TWA: 1000 ppm | | |
| | | TWA: 2950 mg/m ³ | | |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eve/face ProtectionWear appropriate protective eveglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid

Appearance Colorless - Light yellow
Odor No information available
Odor Threshold No information available

Odor ThresholdNo information availablepHNo information availableMelting Point/RangeNo data available

Melting Point/Range

Boiling Point/Range

Flash Point

Evaporation Rate

No data available

No information available

-49 °C / -56.2 °F

Evaporation Rate

No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper
LowerNo data available
No data availableVapor Pressure<=1100 hPa @ 50 °C</th>Vapor DensityNo information available

Specific Gravity 0.652 g/cm3

Solubility
Partition coefficient; n-octanol/water
No information available
No data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

Molecular FormulaC4 H9 LiMolecular Weight64.06

10. Stability and reactivity

Reactive Hazard Yes

Stability Air sensitive. Moisture sensitive. May form precipitate.

Conditions to Avoid Exposure to moist air or water. Exposure to moisture. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Acids, Alcohols, Oxidizing agent

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Lithium oxide

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing. Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. **Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation | | |
|-----------|-------------------------|----------------------------|---------------------------------------|--|--|
| Pentane | LD50 > 2000 mg/kg (Rat) | LD50 = 3000 mg/kg (Rabbit) | LC50 = 364 g/m ³ (Rat) 4 h | | |
| | | | | | |

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available Sensitization No information available

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

| Component | CAS-No | IARC | NTP | ACGIH | OSHA | Mexico |
|----------------------|----------|------------|------------|------------|------------|------------|
| Pentane | 109-66-0 | Not listed |
| Lithium, | 594-19-4 | Not listed |
| (1,1-dimethylethyl)- | | | | | | |

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

No information available. **Teratogenicity**

STOT - single exposure Respiratory system Central nervous system (CNS)

None known STOT - repeated exposure

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|-----------|------------------|-------------------------|------------|------------------------|
| Pentane | Not listed | LC50: = 9.99 mg/L, 96h | Not listed | EC50: = 9.74 mg/L, 48h |
| | | (Lepomis macrochirus) | | (Daphnia magna) |
| | | LC50: = 11.59 mg/L, 96h | | |
| | | (Pimephales promelas) | | |
| | | LC50: = 9.87 mg/L, 96h | | |
| | | (Oncorhynchus mykiss) | | |
| | | | | |

Persistence and Degradability May persist based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility

Is not likely mobile in the environment due its low water solubility.

| Component | log Pow |
|-----------|---------|
| Pentane | 3.39 |

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Technical Name (tert-Butyllithium)

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

TDG

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

<u>IATA</u>

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

IMDG/IMO

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

15. Regulatory information

United States of America Inventory

| Component | CAS-No | TSCA | TSCA Inventory notification - Active/Inactive | TSCA - EPA Regulatory Flags |
|-------------------------------|----------|------|--|--------------------------------|
| Pentane | 109-66-0 | Х | ACTIVE | - |
| Lithium, (1,1-dimethylethyl)- | 594-19-4 | X | ACTIVE | - |

Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

| Component | CAS-No | DSL | NDSL | EINECS | PICCS | ENCS | AICS | IECSC | KECL |
|-----------|----------|-----|------|-----------|-------|------|------|-------|----------|
| Pentane | 109-66-0 | X | - | 203-692-4 | Χ | X | Х | Х | KE-27968 |

| Lithium, (1,1-dimethylethyl)- | 594-19-4 | - | X | 209-831-5 | X | X | Χ | Х | 2014-3-6117 |
|-------------------------------|----------|---|---|-----------|---|---|---|---|-------------|

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

| | Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island | |
|---|-----------|---------------|------------|--------------|----------|--------------|--|
| Г | Pentane | X | X | Χ | - | Х | |

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

| Component | DHS Chemical Facility Anti-Terrorism Standard | | | |
|-----------|---|--|--|--|
| Pentane | Release STQs - 10000lb | | | |

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

Revision Date 28-Feb-2020 Print Date 28-Feb-2020

Revision Summary SDS authoring systems update, replaces ChemGes SDS No. 2,291.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS