

## SAFETY DATA SHEET

Version 8.2  
Revision Date 09/12/2021  
Print Date 06/01/2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Deuterium sulfide

Product Number : 486523  
Brand : Aldrich  
CAS-No. : 13536-94-2

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765  
Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-  
527-3887 CHEMTREC (International) 24  
Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable gases (Category 1), H220  
Gases under pressure (Liquefied gas), H280  
Acute toxicity, Inhalation (Category 1), H330  
Short-term (acute) aquatic hazard (Category 1), H400  
Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 GHS Label elements, including precautionary statements**

Pictogram



Signal word

Danger

Hazard statement(s)	
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H330	Fatal if inhaled.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P284	Wear respiratory protection.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	Eliminate all ignition sources if safe to do so.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	: D <sub>2</sub> S
Molecular weight	: 36.09 g/mol
CAS-No.	: 13536-94-2

Component	Classification	Concentration
<b>Deuterium sulfide</b>		
	Flam. Gas 1; Press. Gas Liquefied gas; Acute Tox. 1; Aquatic Acute 1; Aquatic Chronic 1; H220, H280, H330, H400, H410 M-Factor - Aquatic Acute: 10 M-Factor - Aquatic Chronic: 10	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

Sulfur oxides

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

### 5.4 Further information

Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

## **6.2 Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## **6.3 Methods and materials for containment and cleaning up**

Clean up promptly by sweeping or vacuum.

## **6.4 Reference to other sections**

For disposal see section 13.

---

# **SECTION 7: Handling and storage**

## **7.1 Precautions for safe handling**

### **Advice on safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

### **Advice on protection against fire and explosion**

Use explosion-proof equipment. **Advice on protection against fire and explosion**  
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

### **Hygiene measures**

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

For precautions see section 2.2.

## **7.2 Conditions for safe storage, including any incompatibilities**

### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place.  
Store under inert gas. hygroscopic

### **Storage class**

Storage class (TRGS 510): 2A: Gases

## **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

# **SECTION 8: Exposure controls/personal protection**

## **8.1 Control parameters**

### **Ingredients with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Deuterium sulfide	13536-94-2	TWA	1 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	5 ppm	USA. ACGIH Threshold Limit Values (TLV)
		C	10 ppm 15 mg/m3	USA. NIOSH Recommended Exposure Limits
		CEIL	20 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Peak	50 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		STEL	15 ppm 21 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	10 ppm 14 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	15 ppm 21 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		C	50 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		PEL	10 ppm 14 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

## 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a) Appearance	Form: Liquefied gas
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	-85 °C (-121 °F)
f) Initial boiling point and boiling range	-60 °C -76 °F at 1013 hPa
g) Flash point	( )No data available
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 46 %(V) Lower explosion limit: 4 %(V)
k) Vapor pressure	17,374 hPa at 252 °C (486 °F)
l) Vapor density	1.17 - (Air = 1.0)
m) Density	No data available
Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

### 9.2 Other safety information

Aldrich - 486523

Page 6 of 10

Relative vapor  
density

1.17 - (Air = 1.0)

---

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

No data available

### **10.2 Chemical stability**

Stable under recommended storage conditions.

### **10.3 Possibility of hazardous reactions**

No data available

### **10.4 Conditions to avoid**

Avoid moisture.

Heat, flames and sparks.

### **10.5 Incompatible materials**

Strong oxidizing agents

### **10.6 Hazardous decomposition products**

In the event of fire: see section 5

---

## **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

#### **Acute toxicity**

Oral: No data available

Inhalation: No data available

Dermal: No data available

#### **Skin corrosion/irritation**

No data available

#### **Serious eye damage/eye irritation**

No data available

#### **Respiratory or skin sensitization**

No data available

#### **Germ cell mutagenicity**

No data available

#### **Carcinogenicity**

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

**Specific target organ toxicity - single exposure**

No data available

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**11.2 Additional Information**

Hydrogen sulfide is strongly bound to methemoglobin in a manner similar to cyanide. Toxicologically, its reaction with enzymes in the blood stream inhibits cell respiration resulting in pulmonary paralysis, sudden collapse, and death. It is recognized by its characteristic odor of "rotten eggs". The detectable, minimum perceptible odor occurs at 0.13ppm, rapid olfactory fatigue can occur at high concentrations (>100 ppm). At concentrations of 20ppm hydrogen sulfide begins acting as an irritant on the mucous membranes of the eyes and respiratory tract and increases with concentration and exposure time. Eye irritation is characterized by irritation of the conjunctiva with photophobia to keratoconjunctivitis and vesiculation of the cornea epithelium. Prolonged exposure to moderate concentrations (250ppm) may cause pulmonary edema. At concentrations over 500ppm, drowsiness, dizziness, excitement, headache, unstable gait, and other systemic symptoms occur within a few minutes. Sudden loss of consciousness without premonition, anxiety, or sense of struggle are characteristic of acute exposure at concentrations above 700ppm. At concentrations of 1000-2000ppm hydrogen sulfide is rapidly absorbed through the lung into the blood. In this range a single inhalation may cause coma and may be rapidly fatal. Initially hyperpnea occurs, followed by rapid collapse and respiratory inhibition. At higher concentrations, hydrogen sulfide exerts an immediate paralyzing effect on the respiratory centers. When concentration reaches 5000ppm, imminent death almost always results., Exposure to and/or consumption of alcohol may increase toxic effects.

---

**SECTION 12: Ecological information****12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.



---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

#### Contaminated packaging

Dispose of as unused product.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 1053 Class: 2.3 (2.1)  
Proper shipping name: Hydrogen sulfide  
Reportable Quantity (RQ): 100 lbs  
Poison Inhalation Hazard: Hazard Zone D

### IMDG

UN number: 1053 Class: 2.3 (2.1)  
Proper shipping name: HYDROGEN SULPHIDE  
Marine pollutant : yes

EMS-No: F-D, S-U

### IATA

UN number: 1053 Class: 2.3 (2.1)  
Proper shipping name: Hydrogen sulphide  
IATA Passenger: Not permitted for transport  
IATA Cargo: Not permitted for transport

---

## SECTION 15: Regulatory information

### SARA 302 Components

The following components are subject to reporting levels established by SARA Title III, Section 302:

Deuterium sulfide

CAS-No.

13536-94-2

Revision Date

2013-02-08

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Deuterium sulfide

CAS-No.

13536-94-2

Revision Date

2013-02-08

### SARA 311/312 Hazards

Fire Hazard, Sudden Release of Pressure Hazard, Acute Health Hazard

### Massachusetts Right To Know Components

Aldrich - 486523

Page 9 of 10

Deuterium sulfide	CAS-No. 13536-94-2	Revision Date 2013-02-08
-------------------	-----------------------	-----------------------------

No components are subject to the Massachusetts Right to Know Act.

**Pennsylvania Right To Know Components**

Deuterium sulfide	CAS-No. 13536-94-2	Revision Date 2013-02-08
-------------------	-----------------------	-----------------------------

Deuterium sulfide	CAS-No. 13536-94-2	Revision Date 2013-02-08
-------------------	-----------------------	-----------------------------

**New Jersey Right To Know Components**

Deuterium sulfide	CAS-No. 13536-94-2	Revision Date 2013-02-08
-------------------	-----------------------	-----------------------------

---

**SECTION 16: Other information**

**Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 8.2

Revision Date: 09/12/2021

Print Date: 06/01/2022