

SAFETY DATA SHEET

Version 8.2
Revision Date 10/26/2021
Print Date 03/01/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : o-Xylene

Product Number : 40201
Brand : Supelco
Index-No. : 601-022-00-9
CAS-No. : 95-47-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226
Acute toxicity, Inhalation (Category 4), H332
Acute toxicity, Dermal (Category 4), H312
Skin irritation (Category 2), H315
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
Aspiration hazard (Category 1), H304
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H312 + H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : C₈H₁₀
Molecular weight : 106.17 g/mol
CAS-No. : 95-47-6
EC-No. : 202-422-2
Index-No. : 601-022-00-9

| Component | Classification | Concentration |
|-----------|----------------|---------------|
|-----------|----------------|---------------|

Supelco - 40201

Page 2 of 11

| o-xylene | | |
|-----------------|---|----------|
| | Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 3; H226, H332, H312, H315, H319, H335, H304, H401, H412 Concentration limits: >= 20 %: STOT SE 3, H335; | <= 100 % |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.
Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage stability

Recommended storage temperature
2 - 8 °C

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis |
|-----------|---------|--|----------------------------------|--|
| o-xylene | 95-47-6 | ST | 150 ppm 655 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | TWA | 100 ppm 435 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | TWA | 100 ppm 435 mg/m ³ | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | | TWA | 100 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Remarks | Not classifiable as a human carcinogen | | |
| | | STEL | 150 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | Not classifiable as a human carcinogen | | |

Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|-----------|---------|--|-------------------|---------------------|---|
| o-xylene | 95-47-6 | Methylhippuric acids | 1.5g/g creatinine | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | End of shift (As soon as possible after exposure ceases) | | | |

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|--|
| a) Appearance | Form: liquid Color: colorless |
| b) Odor | aromatic |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point: -25.2 °C (-13.4 °F) at 1,013 hPa |
| f) Initial boiling point and boiling range | 144.5 °C 292.1 °F at 1,013 hPa |
| g) Flash point | 32.0 °C (89.6 °F) - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 6.7 %(V) Lower explosion limit: 0.9 %(V) |
| k) Vapor pressure | 13.37 hPa at 32.22 °C (90.00 °F) |
| l) Vapor density | No data available |
| m) Density | 0.88 g/cm ³ at 25 °C (77 °F) |
| Relative density | No data available |
| n) Water solubility | 0.1705 g/l at 25 °C (77 °F) - partly soluble |
| o) Partition coefficient: n-octanol/water | log Pow: 3.12 at 20 °C (68 °F) - Bioaccumulation is not expected. |

- | | |
|------------------------------|------------------------------|
| p) Autoignition temperature | 463 °C (865 °F) at 1,013 hPa |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | none |

9.2 Other safety information

| | |
|-----------------|--------------------------------|
| Surface tension | 29.8 mN/m at 25.0 °C (77.0 °F) |
|-----------------|--------------------------------|

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:
Strong oxidizing agents
conc. sulfuric acid
Nitric acid
uranium hexafluoride
sulfur

10.4 Conditions to avoid

Heat, flames and sparks.
Heating.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 3,523 mg/kg
(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))
LC50 Inhalation - Rat - male and female - 4 h - 27.12 mg/l - vapor

(US-EPA)

Symptoms: Inhalation may lead to the formation of oedemas in the respiratory tract.
Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

LD50 Dermal - Rabbit - male - 12,126 mg/kg

Remarks: (ECHA)

Supelco - 40201

Page 7 of 11

(Regulation (EC) No 1272/2008, Annex VI)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: Regulation (EC) No. 440/2008, Annex, B.19

Result: negative

Test Type: Mutagenicity (mammal cell test): micronucleus.

Species: Mouse

Cell type: Red blood cells (erythrocytes)

Application Route: Intraperitoneal

Method: OECD Test Guideline 474

Result: negative

Remarks: (IUCLID)

Test Type: dominant lethal test

Species: Mouse

Application Route: Subcutaneous

Method: OECD Test Guideline 478

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 90 Days - NOAEL (No observed adverse effect level) - 200 mg/kg

RTECS: ZE2450000

narcosis, Lung irritation, chest pain, pulmonary edema, Central nervous system depression, Dermatitis, Gastrointestinal disturbance, Liver injury may occur., Kidney injury may occur., Blood disorders

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Nerves. -

SECTION 12: Ecological information

12.1 Toxicity

| | |
|------------------|--|
| Toxicity to fish | static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2.60 mg/l - 96 h (OECD Test Guideline 203) |
|------------------|--|

| | |
|-------------------|--|
| Toxicity to algae | static test EC50 - Pseudokirchneriella subcapitata - 4.36 mg/l - 73 h (OECD Test Guideline 201) |
|-------------------|--|

| | |
|----------------------|-------------------------------|
| Toxicity to bacteria | Remarks: (ECHA) (o-xylene) |
|----------------------|-------------------------------|

12.2 Persistence and degradability

| | |
|------------------|---|
| Biodegradability | aerobic - Exposure time 28 d Result: 94 % - Readily biodegradable. (OECD Test Guideline 301F) |
|------------------|---|

| | |
|---------------------------|-------------------------------|
| Theoretical oxygen demand | 3,125 mg/g Remarks: (Lit.) |
|---------------------------|-------------------------------|

12.3 Bioaccumulative potential

| | |
|-----------------|---|
| Bioaccumulation | Oncorhynchus mykiss (rainbow trout) - 56 d at 10 °C - 1.3 mg/l(o-xylene) |
|-----------------|---|

Bioconcentration factor (BCF): 7.4 - 18.5

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1307 Class: 3 Packing group: III
Proper shipping name: Xylenes
Reportable Quantity (RQ): 1000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1307 Class: 3 Packing group: III EMS-No: F-E, S-D
Proper shipping name: XYLENES

IATA

UN number: 1307 Class: 3 Packing group: III
Proper shipping name: Xylenes

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

| | CAS-No. | Revision Date |
|----------|---------|---------------|
| o-xylene | 95-47-6 | 2007-07-01 |

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.2

Revision Date: 10/26/2021

Print Date: 03/01/2022