



Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Substance
Substance name : Boron trichloride
CAS-No. : 10294-34-5
Formula : BCl3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use; Use as directed.

1.3. Details of the supplier of the safety data sheet

Linde Inc.

10 Riverview Drive

Danbury, CT 06810-6268 - USA

www.lindeus.com

Linde Inc. 1-844-44LINDE (1-844-445-4633)

Linde Electronics 1-800-932-0624 or 1-908-329-9700

1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week

- Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887

(collect calls accepted, Contract 17729)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS US classification

 Press. Gas (Liq.)
 H280

 Acute Tox. 3 (Inhalation:gas)
 H331

 Skin Corr. 1B
 H314

 Eye Dam. 1
 H318

 STOT SE 3
 H335

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)





GHS04

GHS05

GHS06

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

H314 - CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H331 - TOXIC IF INHALED

CGA-HG22 - CORROSIVE TO THE RESPIRATORY TRACT

CGA-HG01 - MAY CAUSE FROSTBITE.

Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe gas/vapors

P262 - Do not get in eyes, on skin, or on clothing. P264 - Wash exposed skin thoroughly after handling

P271+P403 - Use and store only outdoors or in a well-ventilated place.

EN (English US) SDS ID: P-4566 1/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

> P280+P284 - Wear protective gloves, protective clothing, eye protection, respiratory protection, and/or face protection.

P321 - Specific treatment (see First aid measures)

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with container Supplier/owner instructions

CGA-PG05 - Use a back flow preventive device in the piping.

CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and rated for cylinder pressure.

CGA-PG12 - Do not open valve until connected to equipment prepared for use. CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug.

CGA-PG06 - Close valve after each use and when empty.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P311 - Call a poison center or doctor.

P303+P361+P353 - IF ON SKIN OR (HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P336 - Thaw frosted parts with lukewarm water. Do not rub affected area.

P363 - Wash contaminated clothing before reuse.

P310 - Immediately call a poison center or doctor/physician.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Other hazards which do not result in classification

: None.

Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

Substances

Name	Product identifier	%
Boron trichloride (Main constituent)	(CAS-No.) 10294-34-5	100

3.2. **Mixtures**

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician. WARNING: To avoid possible chemical burns, the rescuer should avoid breathing any exhaled air from the victim.

In case of contact, immediately flush affected areas with plenty of water for at least 15 minutes First-aid measures after skin contact while removing contaminated clothing and shoes. Call a physician. Wash clothing before

reuse. Discard contaminated shoes.

Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and First-aid measures after eye contact

away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an

ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: Overexposure to vapor concentrations moderately above 5 ppm irritates the upper respiratory tract. Intolerable concentrations range from 50-100 ppm. High concentrations (greater than 50 ppm) severely irritate the upper respiratory tract, causing the throat to burn and producing choking and coughing. Pulmonary edema; general lung injury; ulceration to the nose, throat, and larynx; and laryngeal spasm may also occur. Exposure to concentrations of 1500-2000 ppm for a few minutes is life-threatening. Liver and kidney injury have been reported after exposure to vapors. At higher concentrations, victim may suffocate from lack of oxygen.

EN (English US) SDS ID: P-4566 2/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Reacts with water.

Special hazards arising from the substance or mixture

: No reactivity hazard other than the effects described in sub-sections below. Reactivity

5.3. **Advice for firefighters**

Firefighting instructions : DANGER! Toxic, corrosive, liquefied gas.

> Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart

L—Fire Protection.

Special protective equipment for fire fighters Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Specific methods Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet

from a protected position. Prevent water used in emergency cases from entering sewers and

drainage systems.

If leaking do not spray water (reacts violently).

Other information Containers are equipped with a pressure relief device. (Exceptions may exist where authorized

by DOT.).

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Danger: Toxic. Corrosive. Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). (gas tight, chemical-protective) Evacuate personnel to a safe area. Approach suspected leak area with caution. Remove all sources of ignition. Toxic, corrosive vapor can spread from spill. Ventilate area or move container to a well-ventilated area. Before entering the area, especially a confined area, check the atmosphere with an appropriate device. Prevent from entering sewers, basements and workpits, or any place where

its accumulation can be dangerous.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

Environmental precautions 6.2.

> Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations.

Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

Reference to other sections 6.4.

See also sections 8 and 13.





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Do not breathe gas/vapor. Avoid all contact with skin, eyes, or clothing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Boron trichloride (10294-34-5)			
ACGIH	ACGIH OEL Ceiling [ppm]	0.7 ppm	
ACGIH	Not established		
USA OSHA	Not established		

8.2. Exposure controls

Appropriate engineering controls

: Use corrosion-proof equipment. USE ONLY IN A CLOSED SYSTEM. An explosion-proof, corrosion-resistant, forced-draft fume hood is preferred.

Eye protection

: Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections. Provide readily accessible eye wash stations and safety showers. Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections.

Skin and body protection

: Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

EN (English US) SDS ID: P-4566 4/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

Respiratory protection

: When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Molecular mass : 117 g/mol

Color : Gives off white fumes in moist air.

Odor : Pungent.

Odor threshold : No data available pH : Not applicable.
Relative evaporation rate (butyl acetate=1) : No data available Relative evaporation rate (ether=1) : Not applicable.
Melting point : -107 °C

Freezing point : No data available

Boiling point : 12.4 °C

Flash point : Not applicable.

Critical temperature : 178.8 °C

Auto-ignition temperature : Not applicable.

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapor pressure : 1.317 bar , 19.1 psia (70°F/21.1°C)

Critical pressure : 3870 kPa
Relative vapor density at 20 °C : No data available

Relative density : 1.3
Relative gas density : 4

Solubility : Water: No data available

Partition coefficient n-octanol/water (Log Pow) : Not applicable.

Partition coefficient n-octanol/water (Log Kow) : Not applicable.

Viscosity, kinematic : Not applicable.

Viscosity, dynamic : Not applicable.

Explosive properties : Not applicable.

Oxidizing properties : None.

Explosion limits : Non flammable.

9.2. Other information

Gas group : Press. Gas (Liq.)

Additional information : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

EN (English US) SDS ID: P-4566 5/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

10.3.	Possibility of hazardous reactions	
		May occur. REACTS VIOLENTLY WITH WATER.
10.4.	Conditions to avoid	
		Avoid moisture in installation systems.
10.5.	Incompatible materials	
		Water. Avoid all organic materials. Hydrogen. Ammonia. Oxygen. Alcohols. Nitrogen peroxide.
10.6.	Hazardous decomposition products	
		Thermal decomposition may produce: Toxic fumes. Chlorides. Hydrochloric acid. Boric acid. Grease. Reacts with water to form toxic and corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Boron trichloride (\f)10294-34-5	
LC50 Inhalation - Rat [ppm]	2541 ppm/1h
ATE US (gases)	1270.5 ppmV/4h

Skin corrosion/irritation : Causes severe skin burns.

pH: Not applicable.

Serious eye damage/irritation : CAUSES SERIOUS EYE DAMAGE.

pH: Not applicable.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : MAY CAUSE RESPIRATORY IRRITATION.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : Overexposure to vapor concentrations moderately above 5 ppm irritates the upper respiratory

tract. Intolerable concentrations range from 50-100 ppm. High concentrations (greater than 50 ppm) severely irritate the upper respiratory tract, causing the throat to burn and producing choking and coughing. Pulmonary edema; general lung injury; ulceration to the nose, throat, and larynx; and laryngeal spasm may also occur. Exposure to concentrations of 1500-2000 ppm for a few minutes is life-threatening. Liver and kidney injury have been reported after exposure to vapors. At higher concentrations, victim may suffocate from lack of oxygen.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No known ecological damage caused by this product.

12.2. Persistence and degradability

Boron trichloride (10294-34-5)	
Persistence and degradability	Not applicable for inorganic gases.

12.3. Bioaccumulative potential

Boron trichloride (10294-34-5)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No data available.

EN (English US) SDS ID: P-4566 6/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

12.4. Mobility in soil

Boron trichloride (10294-34-5)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on ozone layer : None.

Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

In accordance with DOT

Transport document description (DOT) : UN1741 Boron trichloride, 2.3

UN-No.(DOT) : UN1741

Proper Shipping Name (DOT) : Boron trichloride

Class (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115

Hazard labels (DOT) : Poison Gas

2.3 - Poison gas



DOT Special Provisions (49 CFR 172.102)

: 3 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone C (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

B9 - Bottom outlets are not authorized.

B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.

Additional information

Emergency Response Guide (ERG) Number : 125

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided)

is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1741
Class (IMDG) : 2 - Gases
MFAG-No : 125

EN (English US) SDS ID: P-4566 7/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

Air transport

UN-No. (IATA) : 1741 Class (IATA) : 2

Civil Aeronautics Law : Gases under pressure/Gases toxic under pressure

SECTION 15: Regulatory information

15.1. US Federal regulations

Boron trichloride (10294-34-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on the United States SARA Section 302		
Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	500 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb	
SARA Section 313 - Emission Reporting	1 %	

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

CANADA

Boron trichloride (10294-34-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Boron trichloride (10294-34-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

15.2.2. National regulations

Boron trichloride (10294-34-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Boron trichloride(10294-34-5)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No

EN (English US) SDS ID: P-4566 8/10





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

Boron trichloride(10294-34-5)	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S Pennsylvania - RTK (Right to Know) List





Safety Data Sheet P-4566

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 01/21/2021 Supersedes: 10/13/2016 Version: 1.0

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.

Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from www.lindeus.com. If you have questions regarding Linde SDSs, would like the document number and date of the latest SDS, or would like the names of the Linde suppliers in your area, phone or write the Linde Call Center (Phone: 1-800-772-9247; Address: Linde Call Center, Linde Inc. P.O. Box 44, Tonawanda, NY 14151-0044).

Linde, Praxair, the Linde wordmark and the Flowing Airstream design are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.


Copyright © 2020, Linde plc.

Revision date : 01/21/2021

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



SDS US GHS DUAL BRANDED LINDE->PRAXAIR

NFPA fire hazard

NFPA instability

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.